

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.06.2020

Version number 6

Revision: 07.06.2020

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

· **1.1 Product identifier**

· **Trade name: BRUNOX® epoxy® - AEROSOL**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category**

PC9a Coatings and paints, thinners, paint removers

PC14 Metal surface treatment products

· **Process category**

PROC5 Mixing or blending in batch processes

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring

· **Environmental release category**

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

· **Application of the substance / the mixture** Coating material

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

BRUNOX Korrosionsschutz GmbH

Adlzreiterstrasse 13, 85051 Ingolstadt

Postfach 100127 , 85001 Ingolstadt

Tel. + 49/ (0) 841 961 29 04

Fax + 49/ (0) 841 961 29 13

E-mail: office@brunox.com

UFI info / E-mail: ufi@brunox.com

www.brunox.de

BRUNOX AG

Tunnelstrasse 6

CH - 8732 Neuhaus/SG

Tel. +41/ (0)55 285 80 80

Fax +41/ (0)55 285 80 81

E-mail: office@brunox.com

www.brunox.swiss

UFI info / E-mail: ufi@brunox.com

(Contd. on page 2)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.06.2020

Version number 6

Revision: 07.06.2020

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 1)

Further information obtainable from:

Abteilung Produktsicherheit / Product Safety Department:

Tel. - Switzerland: +41/ (0)55 285 80 80

Tel. - Germany: +49 / (0)841 961 29 04

Mo - Do / Mon - Thu: 08:00 - 16:00 Uhr

Fr / Fri: 08:00 - 12:00 Uhr

1.4 Emergency telephone number:

Toxikologisches Informationszentrum

CH - 8030 Zürich, Freiestrasse 16

Tel. +41/ 044 251 51 51

Notruf - CH, STIZ : 145

Notruf - D - : Giftnotrufzentrale 030 19240

Notruf - BE - : 070 -245 245

EUROPÄISCHE NOTRUFNR. : 112

Notruf - GB - : 844 892 0111

Notruf - IE - : + 353 1 837 9964 (medical professionals); + 353 1 809 2166 (public)

Notruf - IS - : + 354 543 22 22

Notruf - JP - : + 81 72 727 2499; + 81 29 852 9999

Notruf - NZ - : 0800 764 766

Notruf - PK - : + 92 21 9920509; + 92 21 35686535

Notruf - PH - : + 632 524 10 78; + 632 544 84 00; local 2311

Notruf - SA - : + 966 146 77 353, + 966 3 8155 646; Ext. 280, 282, 283

Notruf - TH - : + 66 201 1086

Notruf - UAE - : 800 424

Notruf - ZA - : + 27 824 910 160

*

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 3)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.06.2020

Version number 6

Revision: 07.06.2020

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 2)

Hazard pictograms

GHS02 GHS07

Signal word Danger**Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 115-10-6	dimethyl ether	25-50%
EINECS: 204-065-8	⚠ Flam. Gas 1, H220	
Reg.nr.: 01-2119472128-37-XXXX	⚠ Press. Gas (Comp.), H280	
CAS: 67-64-1	acetone	≥10-<20%
EINECS: 200-662-2	⚠ Flam. Liq. 2, H225	
Reg.nr.: 01-2119471330-49-XXXX	⚠ Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 107-98-2	1-methoxy-2-propanol	2.5-10%
EINECS: 203-539-1	⚠ Flam. Liq. 3, H226	
Reg.nr.: 01-2119457435-35-XXXX	⚠ STOT SE 3, H336	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	2.5-10%
EINECS: 203-603-9	⚠ Flam. Liq. 3, H226	
Reg.nr.: 01-2119475791-29-XXXX		

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.06.2020

Version number 6

Revision: 07.06.2020

Trade name: BRUNOX® epoxy® - AEROSOL

CAS: 67-63-0	propan-2-ol	(Contd. of page 3) ≥2.5-<10%
EINECS: 200-661-7	⚠ Flam. Liq. 2, H225	
Reg.nr.: 01-2119457558-25-XXXX	⚠ Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 112-34-5	2-(2-butoxyethoxy)ethanol	≥2.5-<10%
EINECS: 203-961-6	⚠ Eye Irrit. 2, H319	
Reg.nr.: 01-2119475104-44-XXXX		
CAS: 64-18-6	formic acid	<2%
EINECS: 200-579-1	⚠ Acute Tox. 3, H331	
Reg.nr.: 01-2119491174-37-XXXX	⚠ Skin Corr. 1C, H314	
	⚠ Acute Tox. 4, H302	

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information:**

Take affected persons out into the fresh air.
Do not leave affected persons unattended.
Position and transport stably in side position.
Seek medical treatment.

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.
A person vomiting while laying on their back should be turned onto their side.

· 4.2 Most important symptoms and effects, both acute and delayed

Dizziness

Dizziness

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

· 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

· 5.3 Advice for firefighters

· **Protective equipment:**

Do not inhale explosion gases or combustion gases.
Wear self-contained respiratory protective device.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.06.2020

Version number 6

Revision: 07.06.2020

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 4)

· Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Use only in well ventilated areas.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities**· Storage:****· Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Store away from foodstuffs.**· Further information about storage conditions:**

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.06.2020

Version number 6

Revision: 07.06.2020

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 5)

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

CAS: 115-10-6 dimethyl ether

WEL (Great Britain) Short-term value: 958 mg/m³, 500 ppm
Long-term value: 766 mg/m³, 400 ppm

NES (Australia) Short-term value: 950 mg/m³, 500 ppm
Long-term value: 760 mg/m³, 400 ppm

WES (Australia) Short-term value: 950 mg/m³, 500 ppm
Long-term value: 760 mg/m³, 400 ppm

WES (New Zealand) Short-term value: 958 mg/m³, 500 ppm
Long-term value: 766 mg/m³, 400 ppm

CAS: 67-64-1 acetone

WEL (Great Britain) Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

NES (Australia) Short-term value: 2375 mg/m³, 1000 ppm
Long-term value: 1185 mg/m³, 500 ppm

WES (Australia) Short-term value: 2375 mg/m³, 1000 ppm
Long-term value: 1185 mg/m³, 500 ppm

WES (New Zealand) Short-term value: 2375 mg/m³, 1000 ppm
Long-term value: 1185 mg/m³, 500 ppm
bio

CAS: 107-98-2 1-methoxy-2-propanol

WEL (Great Britain) Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm
Sk

NES (Australia) Short-term value: 553 mg/m³, 150 ppm
Long-term value: 369 mg/m³, 100 ppm

WES (Australia) Short-term value: 553 mg/m³, 150 ppm
Long-term value: 369 mg/m³, 100 ppm

WES (New Zealand) Short-term value: 553 mg/m³, 150 ppm
Long-term value: 369 mg/m³, 100 ppm

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

WEL (Great Britain) Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

NES (Australia) Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.06.2020

Version number 6

Revision: 07.06.2020

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 6)

WES (Australia) Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

CAS: 67-63-0 propan-2-ol

WEL (Great Britain) Short-term value: 1250 mg/m³, 500 ppm
Long-term value: 999 mg/m³, 400 ppm

NES (Australia) Short-term value: 1230 mg/m³, 500 ppm
Long-term value: 983 mg/m³, 400 ppm

WES (Australia) Short-term value: 1230 mg/m³, 500 ppm
Long-term value: 983 mg/m³, 400 ppm

WES (New Zealand) Short-term value: 1230 mg/m³, 500 ppm
Long-term value: 983 mg/m³, 400 ppm

CAS: 112-34-5 2-(2-butoxyethoxy)ethanol

WEL (Great Britain) Short-term value: 101.2 mg/m³, 15 ppm
Long-term value: 67.5 mg/m³, 10 ppm

CAS: 64-18-6 formic acid

WEL (Great Britain) Long-term value: 9.6 mg/m³, 5 ppm

NES (Australia) Short-term value: 19 mg/m³, 10 ppm
Long-term value: 9.4 mg/m³, 5 ppm

WES (Australia) Short-term value: 19 mg/m³, 10 ppm
Long-term value: 9.4 mg/m³, 5 ppm

WES (New Zealand) Short-term value: 19 mg/m³, 10 ppm
Long-term value: 9.4 mg/m³, 5 ppm

· **Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

Respiratory protection:

Short term filter device:

Filter A/P2

Filter AX

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Check the permeability prior to each renewed use of the glove.

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.06.2020

Version number 6

Revision: 07.06.2020

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 7)



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed goggles

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information****Appearance:****Form:**

Aerosol

Colour:

Amber coloured

Odour:

Characteristic

Odour threshold:

Not determined.

pH-value at 20 °C (68 °F):

4.8

Change in condition**Melting point/freezing point:**

Undetermined.

Initial boiling point and boiling range: 82 °C (179.6 °F)**Flash point:**

Not applicable, as aerosol.

Flammability (solid, gas):

Not applicable.

Ignition temperature:

235 °C (455 °F)

(Contd. on page 9)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.06.2020

Version number 6

Revision: 07.06.2020

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 8)

- **Decomposition temperature:** Not determined.
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Explosion limits:**
 - Lower:** 2.6 Vol %
 - Upper:** 18.6 Vol %
- **Vapour pressure at 20 °C (68 °F):** 5,200 hPa (3,900.3 mm Hg)
- **Density at 20 °C (68 °F):** 1 g/cm³ (8.345 lbs/gal)
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not applicable.
- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
 - Organic solvents:** 67.5 %
 - Water:** 16.4 %
 - VOC (EC)** 67.54 %
- **Solids content:** 1.5 %
- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB
(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.06.2020

Version number 6

Revision: 07.06.2020

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 9)

SECTION 11: Toxicological information· **11.1 Information on toxicological effects**· **Acute toxicity** Based on available data, the classification criteria are not met.· **LD/LC50 values relevant for classification:****ATE (Acute Toxicity Estimates)**

Oral LD50 61,315 mg/kg (rat)

Inhalative LC50/4 h 50.9 mg/l

CAS: 67-64-1 acetone

Oral LD50 5,800 mg/kg (rat)

Dermal LD50 >15,800 mg/kg (rat)
20,000 mg/kg (rabbit)

Inhalative LC50/4 h 76 mg/l (rat)

CAS: 107-98-2 1-methoxy-2-propanol

Oral LD50 5,660 mg/kg (rat)

Dermal LD50 13,000 mg/kg (rabbit)

Inhalative LC50/4 h 6 mg/l (rat)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8,532 mg/kg (rat)

Dermal LD50 >5,000 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

CAS: 67-63-0 propan-2-ol

Oral LD50 5,045 mg/kg (rat)

Dermal LD50 12,800 mg/kg (rabbit)

Inhalative LC50/4 h 30 mg/l (rat)

CAS: 112-34-5 2-(2-butoxyethoxy)ethanol

Oral LD50 5,660 mg/kg (rat)

Dermal LD50 4,000 mg/kg (rabbit)

CAS: 64-18-6 formic acid

Oral LD50 1,100 mg/kg (rat)

Inhalative LC50/4 h 3 mg/l (ATE)

· **Primary irritant effect:**· **Skin corrosion/irritation**

Bei längeren und/oder häufigem Hautkontakt sind Reizerscheinungen möglich.

Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis.

· **Serious eye damage/irritation**

Causes serious eye irritation.

· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.06.2020

Version number 6

Revision: 07.06.2020

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 10)

- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
 - CAS: 115-10-6 dimethyl ether**
 - EC50 154.92 mg/kg (algae) (QSAR)
 - >4,400 mg/kg (daphnia)
 - LC50/96 h >4,100 mg/l (fish)
 - EC10 >1,600 mg/l (pseudomonas putida)
 - CAS: 67-64-1 acetone**
 - LC50/48 h 8,800 mg/l (daphnia)
 - CAS: 107-98-2 1-methoxy-2-propanol**
 - EC50 >500 mg/kg (daphnia)
 - LC50/96 h 4,600-10,000 mg/l (leuciscus idus)
 - CAS: 108-65-6 2-methoxy-1-methylethyl acetate**
 - EC50 >500 mg/kg (daphnia)
 - LC50/96 h 160 mg/l (pimephales promelas)
 - CAS: 64-18-6 formic acid**
 - EC50 120 mg/kg (daphnia)
 - LC50/48 h 122 mg/l (leuciscus idus)
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.06.2020

Version number 6

Revision: 07.06.2020



Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 11)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **European waste catalogue**
HP 3 Flammable
HP 4 Irritant - skin irritation and eye damage
- **Uncleaned packaging:**
- **Recommendation:**
Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR/RID/ADN, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR/RID/ADN** 1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- **ADR/RID/ADN**
- 
- **Class** 2.5F Gases.
- **Label** 2.1
- **IMDG, IATA**
- 
- **Class** 2.1
- **Label** 2.1
- **14.4 Packing group**
- **ADR/RID/ADN, IMDG, IATA** Void

(Contd. on page 13)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.06.2020

Version number 6

Revision: 07.06.2020

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 12)

- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **14.6 Special precautions for user**
- **Danger code (Kemler):** -
- **EMS Number:** F-D,S-U
- **Stowage Code** SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
- **Segregation Code**
- **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.
- **Transport/Additional information:**
- **ADR/RID/ADN**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity
- **Transport category** 2
- **Tunnel restriction code** D
- **IMDG**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity
- **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P3a FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

(Contd. on page 14)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.06.2020

Version number 6

Revision: 07.06.2020

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 13)

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H336 May cause drowsiness or dizziness.

- **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1: Flammable gases – Category 1
- Aerosol 1: Aerosols – Category 1
- Press. Gas (Comp.): Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Acute Tox. 3: Acute toxicity – Category 3
- Skin Corr. 1C: Skin corrosion/irritation – Category 1C
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- *** Data compared to the previous version altered.**