

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.05.2021

Version: 2.01

Revision: 22.04.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX Brake & Parts Cleaner

Article number:

04833000, 04833410, 04837410, 08364000-280

UFI: R050-H0TD-C00X-66D0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC35 Washing and cleaning products (including solvent based products)

Application of the substance / the mixture Cleaning material/ Detergent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02

GHS07

GHS09

Signal word Danger

Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane propan-2-ol

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

(Contd. on page 2)

-GB-

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.05.2021

Version: 2.01

Revision: 22.04.2021

Trade name: SONAX Brake & Parts Cleaner

(Contd. of page 1)

H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/eye protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable.

vPvB: Not applicable.

Determination of endocrine-disrupting properties Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures
Description: Preparation of propellant and solvents

Dangerous components:

EC No 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Alternative CAS number: 64742-49-0 ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	50 - <75%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	15 - <20%
CAS: 110-82-7 EINECS: 203-806-2 Reg.nr.: 01-2119463273-41-xxxx	cyclohexane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	5 - <10%
CAS: 124-38-9 EINECS: 204-696-9	carbon dioxide ⚠ Press. Gas (Ref. Liq.), H281	3 - <5%
CAS: 110-54-3 EINECS: 203-777-6 Reg.nr.: 01-2119480412-44-xxxx	n-hexane ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361f; STOT RE 2, H373; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 Specific concentration limit: STOT RE 2; H373: C ≥ 5 %	1 - <3%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

 aliphatic hydrocarbons ≥30%
Additional information:

For the wording of the listed hazard phrases refer to section 16.

Hydrocarbon mixture:

Benzene content < 0.1%

Cyclohexane is a part of the hydrocarbon mixture.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.05.2021

Version: 2.01

Revision: 22.04.2021

Trade name: SONAX Brake & Parts Cleaner*n-Hexane is a part of the hydrocarbon mixture.*

(Contd. of page 2)

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:***Take affected persons out of danger area and lay down.**Remove soiled clothing***After inhalation:***Supply fresh air.**In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.***After skin contact:***Wash the areas of skin affected with water and a mild detergent.**If symptoms persist consult doctor.***After eye contact:** *Rinse opened eye for several minutes under running water. Then consult a doctor.***After swallowing:** *Do not induce vomiting; call for medical help immediately.***4.2 Most important symptoms and effects, both acute and delayed***Headache**Dizziness**Nausea**Drowsiness**Skin irritation**Eye irritation***4.3 Indication of any immediate medical attention and special treatment needed***Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.***SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:***Foam**Carbon dioxide**Fire-extinguishing powder**Water haze***For safety reasons unsuitable extinguishing agents:** *Water with full jet***5.2 Special hazards arising from the substance or mixture***Can form explosive gas-air mixtures.**In case of fire, the following can be released:**Carbon monoxide (CO)**Carbon dioxide (CO₂)***5.3 Advice for firefighters****Protective equipment:***Do not inhale explosion gases or combustion gases.**Wear fully protective suit.**Do not enter the hazardous area without a self-contained breathing apparatus.**See Section 8 for information on personal protection equipment.***Additional information***Cool endangered receptacles with water spray.**Collect contaminated fire fighting water separately. It must not enter the sewage system.***SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures***Keep away from ignition sources.**Ensure adequate ventilation**Wear protective equipment. Keep unprotected persons away.***6.2 Environmental precautions:***Do not allow to penetrate the ground/soil.*

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.05.2021

Version: 2.01

Revision: 22.04.2021

Trade name: SONAX Brake & Parts Cleaner

(Contd. of page 3)

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Buildup of explosive mixtures possible without sufficient ventilation.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Highly volatile, flammable constituents are released during processing.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 67-63-0 propan-2-ol

WEL (Great Britain)	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
---------------------	--

CAS: 110-82-7 cyclohexane

WEL (Great Britain)	Short-term value: 1050 mg/m ³ , 300 ppm Long-term value: 350 mg/m ³ , 100 ppm
IOELV (EU)	Long-term value: 700 mg/m ³ , 200 ppm

CAS: 124-38-9 carbon dioxide

WEL (Great Britain)	Short-term value: 27400 mg/m ³ , 15000 ppm Long-term value: 9150 mg/m ³ , 5000 ppm
IOELV (EU)	Long-term value: 9000 mg/m ³ , 5000 ppm

CAS: 110-54-3 n-hexane

WEL (Great Britain)	Long-term value: 72 mg/m ³ , 20 ppm
---------------------	--

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.05.2021

Version: 2.01

Revision: 22.04.2021

Trade name: SONAX Brake & Parts Cleaner

(Contd. of page 4)

IOELV (EU)	Long-term value: 72 mg/m ³ , 20 ppm	
Regulatory information WEL (Great Britain): EH40/2011		
DNELs		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	DNEL	699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)
Dermal	DNEL	699 mg/kg bw/day (consumer) (chronic exposition / systemi effects) 773 mg/kg bw/day (worker) (chronic exposition / systemic effects)
Inhalative	DNEL	608 mg/m ³ (consumer) (chronic exposition / systemic effects) 2035 mg/m ³ (worker) (chronic exposition / systemic effects)
CAS: 67-63-0 propan-2-ol		
Oral	DNEL	26 mg/kg (consumer) (chornic effects (1d))
Dermal	DNEL	319 mg/kg (consumer) (chronic effects (1d)) 888 mg/kg (worker) (chronic effects (1d))
Inhalative	DNEL	89 mg/m ³ (consumer) (chronic effects) 500 mg/m ³ (worker) (chronic effects)
PNECs		
CAS: 67-63-0 propan-2-ol		
PNEC	140.9 mg/l (sporadic release) 2251 mg/l (STP) 140.9 mg/l (water (fresh water)) 140.9 mg/l (water (sea water))	
PNEC	28 mg/kg (gro) 552 mg/kg (sediment)	

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Hand protection Protective gloves

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

Penetration time of glove material Value for the permeation: Level 6 (≥480min)

Eye/face protection

Safety glasses

[EN 166]

GB

(Contd. on page 6)

Trade name: SONAX Brake & Parts Cleaner

(Contd. of page 5)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Aerosol
Colour:	Colourless
Odour:	Solvent-like
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	60 - 120 °C (Active ingredient data)
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	2 Vol% (propan-2-ol data) Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane: 0,6 Vol. %
Upper:	12 Vol% (propan-2-ol data) 8,0 Vol. % (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane)
Flash point:	< -5 °C (Active ingredient data)
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
pH	Not applicable.
Viscosity:	
Kinematic viscosity	< 20.5 mm ² /s (Daten Wirkstoff)
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	0.72 - 0.74 g/cm ³ (Active ingredient data)
Relative density	Not determined.
Vapour density	Not determined.

9.2 Other information

Appearance:	
Form:	Aerosol
Important information on protection of health and environment, and on safety.	
Explosive properties:	In use, may form flammable/explosive vapour-air mixture.
Change in condition	
Evaporation rate	Not applicable.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	
Extremely flammable aerosol. Pressurised container: May burst if heated.	
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.05.2021

Version: 2.01

Revision: 22.04.2021

Trade name: SONAX Brake & Parts Cleaner

(Contd. of page 6)

Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.

10.4 Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

An increase in pressure may lead to bursting.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials:

strong oxidizing agents

strong acids

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral	LD50	>5000 mg/kg (rat) (OECD 401)
------	------	------------------------------

Dermal	LD50	>2000 mg/kg (rat) (OECD 402)
--------	------	------------------------------

Inhalative	LC50 / 4h	>20 mg/l (rat) (OECD 403)
------------	-----------	---------------------------

CAS: 67-63-0 propan-2-ol

Oral	LD50	5840 mg/kg (rat)
------	------	------------------

Dermal	LD50	13900 mg/kg (rabbit)
--------	------	----------------------

Inhalative	LC50 / 6 h	>25 mg/l (rat) (OECD 403)
------------	------------	---------------------------

CAS: 110-82-7 cyclohexane

Oral	LD50	>5000 mg/kg (rabbit)
------	------	----------------------

Dermal	LD50	> 2000 mg/kg (rabbit)
--------	------	-----------------------

Inhalative	LC50 / 4h	>32880 mg/m ³ (rat)
------------	-----------	--------------------------------

CAS: 110-54-3 n-hexane

Oral	LD50	3200 mg/kg (rat)
------	------	------------------

Dermal	LD50	3350 mg/kg (rabbit)
--------	------	---------------------

Inhalative	LC50/4d	172 mg/l (rat)
------------	---------	----------------

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.05.2021

Version: 2.01

Revision: 22.04.2021

Trade name: SONAX Brake & Parts Cleaner

(Contd. of page 7)

Aspiration hazard Based on available data, the classification criteria are not met.**11.2 Information on other hazards****Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Product is considered to be harmful to aquatic organisms. May have long-term harmful effects in aquatic environments.

Aquatic toxicity:**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

LL50 / 96h	11.4 mg/l (Oncorhynchus mykiss) (OECD 203)
EL50 / 48h	3 mg/l (Daphnia magna) (OECD 202)
EL50 / 72h	30 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
LOEC	0.32 mg/l (Daphnia magna) (21d)
NOELR 72 h	3 mg/l (Pseudokirchneriella subcapitata)
NOEC / 21 d	0.17 mg/l (Daphnia magna)

CAS: 67-63-0 propan-2-ol

LC50 / 96h	9640 mg/l (Pimephales promelas)
LC50 / 24h	9714 mg/l (daphnia)
EC50	>100 mg/l (bacteria)
EC50 / 72h	>100 mg/l (algae)

CAS: 110-82-7 cyclohexane

LC50 / 96h	4.53 mg/l (Pimephales promelas)
EC50 / 48h	2.4 mg/l (Daphnia magna)
EC50 / 72h	3.4 mg/l (Pseudokirchneriella subcapitata)

CAS: 110-54-3 n-hexane

LL50 / 96h	12.51 mg/l (Oncorhynchus mykiss)
EL50 / 48h	21.85 mg/l (Daphnia magna)

12.2 Persistence and degradability**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

Biodegradation | 81 % (28d)

CAS: 67-63-0 propan-2-ol

Biodegradation | 53 %

CAS: 110-54-3 n-hexane

Biodegradation | 83 % (10d (ECHA))

12.3 Bioaccumulative potential**CAS: 110-82-7 cyclohexane**

log Kow | 3.44 log Kow (pH: 7, 25°C)

CAS: 110-54-3 n-hexane

log Kow | 4 log Kow (pH: 7, 20°C)

12.4 Mobility in soil

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane:

Highly volatile, will partition rapidly to air.

12.5 Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.05.2021

Version: 2.01

Revision: 22.04.2021

Trade name: SONAX Brake & Parts Cleaner

(Contd. of page 8)

12.7 Other adverse effects

Additional ecological information:

General notes: The product may not be released into the environment without control.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue

Disposal / product + Disposal / contaminated packaging

15 01 10* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number ADR/RID/ADN, IMDG, IATA

UN1950

14.2 UN proper shipping name ADR/RID/ADN IMDG IATA

1950 AEROSOLS
AEROSOLS
AEROSOLS, flammable

14.3 Transport hazard class(es) ADR/RID/ADN



Class 2 5F Gases.
Label 2.1

IMDG, IATA



Class 2.1
Label 2.1

14.4 Packing group ADR/RID/ADN, IMDG, IATA

Void

14.5 Environmental hazards: Marine pollutant:

Yes
absent due to package size =<5l

14.6 Special precautions for user

see Sections 6-8
Warning: Gases.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Transport/Additional information:

ADR/RID/ADN

Limited quantities (LQ) 1L
Transport category 2
Tunnel restriction code D

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.05.2021

Version: 2.01

Revision: 22.04.2021

Trade name: SONAX Brake & Parts Cleaner

(Contd. of page 9)

UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Chemical safety assessment****Catégorie SEVESO (DIRECTIVE 2012/18/EU)**

E2 Hazardous to the Aquatic Environment

P3b FLAMMABLE AEROSOLS

National regulations:**Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H281 Contains refrigerated gas; may cause cryogenic burns or injury.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Aerosols

On basis of test data

Skin corrosion/irritation
Serious eye damage/eye irritation
Specific target organ toxicity (single exposure)
Hazardous to the aquatic environment - long-term (chronic) aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Version number of previous version: 2.00**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = letal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Aerosol 1: Aerosols – Category 1

Press. Gas (Ref. Liq.): Gases under pressure – Refrigerated liquefied gas

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 19.05.2021

Version: 2.01

Revision: 22.04.2021

Trade name: SONAX Brake & Parts Cleaner

(Contd. of page 10)

Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Sources

"Regulation (EC) Nr. 1907/2006 (REACH), 1272/2008 (CLP), 648/2004 (Detergents) in the respective valid version. National occupation exposure limits for each country in the respective valid version. Transportation regulations according to ADR, RID, IMDG, IATA in the respective valid version."

* **Data compared to the previous version altered.**

GB