

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.05.2021

Version: 3.01

Revision: 22.04.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** SONAX AntiFreeze & Clear View ready-to-use Blue-Energy**Article number:** 01324000, 01324410, 01325000**1.2 Relevant identified uses of the substance or mixture and uses advised against****Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category

PC4 Anti-Freeze and de-icing products

PC35 Washing and cleaning products (including solvent based products)

Application of the substance / the mixture Car care product**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk**1.4 Emergency telephone number:****European Union:** +49 (0) 89 19240 (Poison Centre Munich)**United Kingdom:** 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3 H226 Flammable liquid and vapour.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02

Signal word Warning**Hazard statements**

H226 Flammable liquid and vapour.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2021

Version: 3.01

Revision: 22.04.2021

Trade name: SONAX AntiFreeze & Clear View ready-to-use Blue-Energy
Determination of endocrine-disrupting properties Not applicable.

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Aqueous formulation of alcohol, glycol and tensides.

Dangerous components:

CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-xxxx	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	25-<50%
CAS: 107-21-1 EINECS: 203-473-3 Reg.nr.: 01-2119456816-28-xxxx	ethanediol STOT RE 2, H373; Acute Tox. 4, H302	1-<3%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

anionic surfactants	<5%
perfumes	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Remove soiled clothing

After inhalation: Supply fresh air.

After skin contact:

Generally the product does not irritate the skin.

Wash the areas of skin affected with water and a mild detergent.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Water spray

Fire-extinguishing powder

Alcohol resistant foam

Carbon dioxide

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2021

Version: 3.01

Revision: 22.04.2021

Trade name: SONAX AntiFreeze & Clear View ready-to-use Blue-Energy

Additional information

(Contd. of page 2)

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Keep container tightly sealed.

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 64-17-5 ethanol

WEL (Great Britain) Long-term value: 1920 mg/m³, 1000 ppm

CAS: 107-21-1 ethanediol

WEL (Great Britain) Short-term value: 104** mg/m³, 40** ppm
Long-term value: 10* 52** mg/m³, 20** ppm
Sk *particulate **vapour

IOELV (EU) Short-term value: 104 mg/m³, 40 ppm
Long-term value: 52 mg/m³, 20 ppm
Skin

Regulatory information

WEL (Great Britain): EH40/2018

IOELV (EU): (EU) 2017/164

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2021

Version: 3.01

Revision: 22.04.2021

Trade name: SONAX AntiFreeze & Clear View ready-to-use Blue-Energy

(Contd. of page 3)

DNELs
CAS: 64-17-5 ethanol

Oral	DNEL	87 mg/kg (consumer) (long-term exposure - systemic effects)
Dermal	DNEL	206 mg/kg bw/day (consumer) (long-term exposure - systemic effects)
		343 mg/kg bw/day (worker) (long-term exposure - systemic effects)
Inhalative	DNEL	950 mg/m ³ (consumer) (acute short-term exposure - local effects)
		1,900 mg/m ³ (worker) (acute short-term exposure - local effects)
	DNEL	114 mg/m ³ (consumer) (long-term exposure - systemic effects)
		950 mg/m ³ (worker) (long-term exposure - systemic effects)

CAS: 107-21-1 ethanediol

Dermal	DNEL	53 mg/kg bw/day (consumer) (long term (chronic) / systemic)
		106 mg/kg bw/day (worker) (long term (chronic) / systemic)
Inhalative	DNEL	7 mg/m ³ (consumer) (long term (chronic) / local)
		35 mg/m ³ (worker) (long term (chronic) / local)

PNECs
CAS: 64-17-5 ethanol

PNEC	0.96 mg/l (water (fresh water))
	0.79 mg/l (water (sea water))
PNEC	3.6 mg/kg (sediment (fresh water))
	2.9 mg/kg (sediment (sea water))
	0.63 mg/kg (soil)

CAS: 107-21-1 ethanediol

PNEC	199.5 mg/l (STP)
	10 mg/l (water (intermittent release))
	10 mg/l (water (fresh water))
	1 mg/l (water (sea water))
PNEC	1.53 mg/kg (gro)
	37 mg/kg (sediment (fresh water)) (dry weight)
	3.7 mg/kg (sediment (sea water)) (dry weight)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls
Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment
General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

Hand protection Not required in normal cases.

Eye/face protection Not required in normal cases

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties
General Information
Physical state

Fluid

Colour:

Blue

(Contd. on page 5)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.05.2021

Version: 3.01

Revision: 22.04.2021

Trade name: SONAX AntiFreeze & Clear View ready-to-use Blue-Energy

(Contd. of page 4)

Odour:	Sweetish
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	78 - 200 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	3.5 Vol.% (Main ingredient data)
Upper:	15.0 Vol.% (Main ingredient data)
Flash point:	27 °C (DIN 51755)
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
pH	7.5 - 8.5
Viscosity:	
Kinematic viscosity at 40 °C	<20.5 mm²/s
Solubility	
water:	Fully miscible.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	0.96 - 0.97 g/cm³
Relative density	Not determined.
Vapour density	Not determined.

9.2 Other information

Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Change in condition	
Evaporation rate	Not determined.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	
Flammable liquid and vapour.	
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity** No dangerous reactions known.
- 10.2 Chemical stability** Stable under normal conditions.
- 10.3 Possibility of hazardous reactions** Develops readily flammable gases/fumes.
- 10.4 Conditions to avoid**
Keep ignition sources away - Do not smoke.

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2021

Version: 3.01

Revision: 22.04.2021

Trade name: SONAX AntiFreeze & Clear View ready-to-use Blue-Energy

(Contd. of page 5)

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

CAS: 64-17-5 ethanol

Oral	LD50	5,560 mg/kg (guinea pig)
		3,450 mg/kg (mouse)
		7,060 mg/kg (rat)
		6,300 mg/kg (rabbit)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4d	20,000 mg/l (rat)

CAS: 107-21-1 ethanediol

Oral	LD50	7,712 mg/kg (rat)
Dermal	LD50	>3,500 mg/kg (mouse)
Inhalative	LC50 / 6 h	>2.5 mg/l (rat)

Skin corrosion/irritation Based on available data, the classification criteria are not met.**Serious eye damage/irritation** Based on available data, the classification criteria are not met.**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.**Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.

Additional toxicological information:

Repeated dose toxicity

CAS: 64-17-5 ethanol

Oral	LOAEL	3,160 mg/kg (rat)
	NOAEL	1,730 mg/kg (rat)

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxicity:

CAS: 64-17-5 ethanol

LC50 / 48h	8,140 mg/l (Leuciscus idus)
LC50 / 24h	>100 mg/l (Daphnia magna)
EC5 / 16h	6,500 mg/l (Pseudomonas putida)
EC50 / 48h	9,268 mg/l (Daphnia magna)

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2021

Version: 3.01

Revision: 22.04.2021

Trade name: SONAX AntiFreeze & Clear View ready-to-use Blue-Energy

(Contd. of page 6)

CAS: 107-21-1 ethanediol

LC50 / 96h	72,860 mg/l (Pimephales promelas)
EC20 / 0.5 h	>1,995 mg/l (activated sludge)
EC50 / 48h	>100 mg/l (Daphnia magna)
EC50 / 96 h	6,500-13,000 mg/l (Pseudokirchneriella subcapitata)
NOEC / 7 d	8,590 mg/l (Ceriodaphnia Dubia) (EPA 600/4-89/001)
	15,380 mg/l (Pimephales promelas) (EPA 600/4-89/001)

12.2 Persistence and degradability

The surface-active substances contained in the product meet the requirement of the EU Detergent Regulation (EC/648/2004) for ultimate biodegradability for surfactants in detergents.

12.3 Bioaccumulative potential**CAS: 107-21-1 ethanediol**

log POW | 1.36 log POW

12.4 Mobility in soil No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.**12.7 Other adverse effects****Additional ecological information:****General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.**European waste catalogue**

20 01 29* | detergents containing dangerous substances

Uncleaned packaging:

15 01 10*: packaging containing residues of or contaminated by dangerous substances

Recommendation:

Packaging may be reused or recycled after cleaning.

15 01 02: plastic packaging

Recommended cleansing agents: Water**SECTION 14: Transport information****14.1 UN number or ID number**

ADR, IMDG, IATA

UN1170

14.2 UN proper shipping name

ADR

1170 ETHANOL SOLUTION

IMDG, IATA

ETHANOL SOLUTION

14.3 Transport hazard class(es)

ADR, IMDG, IATA

Class
Label3 Flammable liquids.
3

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.05.2021

Version: 3.01

Revision: 22.04.2021

Trade name: SONAX AntiFreeze & Clear View ready-to-use Blue-Energy

(Contd. of page 7)

14.4 Packing group
ADR, IMDG, IATA

III

14.5 Environmental hazards:
Marine pollutant:

No

14.6 Special precautions for user

Warning: Flammable liquids.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ)

5L

Transport category

3

Tunnel restriction code

D/E

UN "Model Regulation":

UN 1170 ETHANOL SOLUTION, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Classification according to Regulation (EC) No 1272/2008

Flammable liquids | On basis of test data

Version number of previous version: 3.00

Abbreviations and acronyms:

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = Lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

(Contd. on page 9)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.05.2021

Version: 3.01

Revision: 22.04.2021

Trade name: SONAX AntiFreeze & Clear View ready-to-use Blue-Energy**Sources**

(Contd. of page 8)

"Regulation (EC) Nr. 1907/2006 (REACH), 1272/2008 (CLP), 648/2004 (Detergents) in the respective valid version. National occupation exposure limits for each country in the respective valid version. Transportation regulations according to ADR, RID, IMDG, IATA in the respective valid version."

* Data compared to the previous version altered.

GB