according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 601

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Lubricant spray

stance/Mixture

Recommended restrictions

on use

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person : mcm@oks-germany.com

responsible for the SDS Material Compliance Management

National contact

1.4 Emergency telephone number

Emergency telephone num: +49 8142 3051 517

ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-

ways.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

Hazard pictograms :





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters air-

ways.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin

dryness or cracking.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha

Additional Labelling

EUH208 Contains Sulfonic acids, petroleum, calcium salts. May produce an allergic reac-

tion.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Active substance with propellant

Mineral oil.



according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration limits M-Factor Notes	Concentration (% w/w)
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naph- tha	64742-48-9 265-150-3 649-327-00-6	Asp. Tox.1; H304	Note P	>= 50 - < 70
Sulfonic acids, petro- leum, calcium salts	61789-86-4 263-093-9 01-2119488992-18- 0000	Skin Sens.1B; H317	>= 10 % Skin Sens.1B,	>= 1 - < 10
Substances with a work				
butane	106-97-8 203-448-7 601-004-00-0 01-2119474691-32- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 10 - < 20
propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1)	>= 1 - < 10
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- XXXX	Not classified	Note L	>= 1 - < 10
distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0 265-169-7 649-474-00-6 01-2119471299-27- XXXX	Not classified	Note L	>= 1 - < 10

For explanation of abbreviations see section 16.



according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial respira-

ion.

In case of skin contact : Take off all contaminated clothing immediately.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes. Seek medical advice.

If swallowed : Move the victim to fresh air.

Keep respiratory tract clear. Do NOT induce vomiting. Obtain medical attention. Rinse mouth with water.

Aspiration hazard if swallowed - can enter lungs and cause

damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Can be absorbed through skin.

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Fire Hazard

Do not let product enter drains.

Contains gas under pressure; may explode if heated.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Hazardous combustion prod: :

ucts

Carbon oxides

Nitrogen oxides (NOx)

Sulphur oxides

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposi-

tion products may be a hazard to health.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Ensure adequate ventilation.
Remove all sources of ignition.

Do not breathe vapours or spray mist.

Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water

according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

courses.

Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn,

even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.



according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

Storage class (TRGS 510) : 2B, Aerosol cans and lighters

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Naphtha (petrole- um), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	AGW	300 mg/m3	DE TRGS 900 (2017-11-30)
Peak-limit: excursion factor (category)	2;(II)			
Further information			on solvent mixtures	
butane	106-97-8	AGW	1.000 ppm 2.400 mg/m3	DE TRGS 900 (2006-01-01)
Peak-limit: excursion factor (category)	4;(II)			
propane	74-98-6	AGW	1.000 ppm 1.800 mg/m3	DE TRGS 900 (2006-01-01)
Peak-limit: excursion factor (category)	4;(II)			
Distillates (petrole- um), hydrotreated heavy paraffinic; Baseoil — un- specified	64742-54-7	AGW (Vapour and aerosols)	5 mg/m3	DE TRGS 900 (2018-06-07)
Peak-limit: excursion factor (category)	4;(II)			
Further information	When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
distillates (petrole- um), solvent- dewaxed heavy paraffinic	64742-65-0	AGW (Vapour and aerosols)	5 mg/m3	DE TRGS 900 (2018-06-07)
Peak-limit: excur-	4;(II)			

according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

sion factor (catego- ry)				
Further information	When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Sulfonic acids, petroleum, calcium salts	61789-86-4	AGW (Alveolate fraction)	5 mg/m3	DE TRGS 900 (2015-11-06)
Peak-limit: excursion factor (category)	4;(II)			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health ef-	Value
			fects	
Distillates (petrole- um), hydrotreated heavy paraffinic; Baseoil — unspecified	Workers	Inhalation	Long-term local effects	5,6 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Distillates (petroleum), hy- drotreated heavy paraffinic; Baseoil — unspecified	Oral	9,33 mg/kg
distillates (petroleum), solvent- dewaxed heavy paraffinic	Oral	9,33 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation. Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374

derived from it.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.



according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

Short term only

Filter type : Filter type A-P

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the spe-

cific work-place.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : brown

Odour : characteristic

Odour Threshold : No data available

pH : substance/mixture is non-soluble (in water)

Melting point/range : No data available

Boiling point/boiling range : < -20 °C

(1.013 hPa)

Flash point : -20 °C

Method: Abel-Pensky, closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

9,4 %(V)

Lower explosion limit / Lower :

flammability limit

0,7 %(V)

Vapour pressure : 2.800 hPa (20 °C)

Relative vapour density : No data available

Relative density : 0,741 (20 °C)

Reference substance: Water

according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

The value is calculated

Density : 0,74 g/cm3

(20 °C)

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm2/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

9.2 Other information

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.



according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : Symptoms: Inhalation may provoke the following symptoms:,

Respiratory disorder

Acute dermal toxicity : Remarks: Prolonged or repeated skin contact with liquid may

cause defatting resulting in drying, redness and possible blis-

tering.

Symptoms: Skin disorders

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5,53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Product:

Remarks : This information is not available.

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : Mild skin irritation

Result : Repeated exposure may cause skin dryness or cracking.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.



according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Sulfonic acids, petroleum, calcium salts:

Assessment : The product is a skin sensitiser, sub-category 1B.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

GLP : yes

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Guinea pig

according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Germ cell mutagenicity- As-

sessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects.

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Genotoxicity in vitro : Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Species: Mouse

Application Route: Oral

Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

Product:

Remarks : No data available

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Carcinogenicity - Assess-

: Not classifiable as a human carcinogen.

ment

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Carcinogenicity - Assess-

ment

: Not classifiable as a human carcinogen.

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Mouse Application Route : Dermal



according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

Method : OECD Test Guideline 451

Result : negative

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal develop-

ment

Remarks: No data available

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Reproductive toxicity - Assessment :

No toxicity to reproduction No toxicity to reproduction

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Reproductive toxicity - As-

sessment

No toxicity to reproduction

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Effects on foetal develop: Species: Rat

ment

Application Route: Dermal

General Toxicity Maternal: NOAEL: 30 mg/kg body weight Developmental Toxicity: NOAEL: 30 mg/kg body weight

Method: OECD Test Guideline 414

STOT - single exposure

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT - repeated exposure

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.



according to Regulation (EC) No. 1907/2006 - DE



OKS 601

Date of last issue: 26.07.2018 Version Revision Date: Print Date: Date of first issue: 06.06.2016 29.06.2021 2.2 29.06.2021

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

May be fatal if swallowed and enters airways.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

No aspiration toxicity classification

distillates (petroleum), solvent-dewaxed heavy paraffinic:

No aspiration toxicity classification

Further information

Product:

Remarks Information given is based on data on the components and

the toxicology of similar products.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Toxicity to fish

Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

according to Regulation (EC) No. 1907/2006 - DE



OKS 601

Version **Revision Date:** Date of last issue: 26.07.2018 Print Date: Date of first issue: 06.06.2016 29.06.2021 2.2 29.06.2021

aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

Exposure time: 72 h

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

> Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h Test Type: Immobilization

Method: OECD Test Guideline 202

GLP: yes

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 10 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test

Method: OECD Test Guideline 211

GLP: yes

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

> Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (green algae)): > 100

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

NOEC: 10 mg/l

Exposure time: 21 d

ic toxicity) Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Product:



according to Regulation (EC) No. 1907/2006 - DE



OKS 601

Version Date of last issue: 26.07.2018 Revision Date: Print Date: 29.06.2021 Date of first issue: 06.06.2016 29.06.2021 2.2

Biodegradability Remarks: No data available

Physico-chemical removabil- : Remarks: No data available

Components:

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Biodegradability Test Type: aerobic

> Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 3 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: yes

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Biodegradability Test Type: aerobic

> Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

Components:

butane:

Partition coefficient: nlog Pow: 2,89

octanol/water Method: OECD Test Guideline 107

propane:

Partition coefficient: n-

octanol/water

log Pow: 2,36

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Partition coefficient: n-

octanol/water

: log Pow: > 2



according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environ-

mental compartments

: Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Assessment : Non-classified PBT substance. Non-classified vPvB sub-

stance.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Assessment : Non-classified vPvB substance. Non-classified PBT sub-

stance.

12.6 Other adverse effects

Product:

Endocrine disrupting poten-

tial

The substance/mixture does not contain components considered to have endocrine disrupting properties according to

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological infor-

mation

No information on ecology is available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.



according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied

16 05 04*, gases in pressure containers (including halons)

containing hazardous substances

SECTION 14: Transport information

14.1 UN number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

ADR

Packing group : Not assigned by regulation

Classification Code : 5F

according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passen- : 203

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.



according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

 This product does not contain substances of very high concern (Regu-

lation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

: Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

34 Petroleum products: (a)

gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

P2

18 Liquefied extremely flam-

mable gases (including LPG) and natural gas



according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

Water contaminating class

(Germany)

WGK 1 slightly hazardous to water

Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : Total dust:

Not applicable

Inorganic substances in powdered form:

Not applicable

Inorganic substances in vapour or gaseous form:

Not applicable

Organic Substances: portion Class 1: 1,02 %

others: 98,48 %

Carcinogenic substances:

Not applicable Mutagenic: Not applicable

Toxic to reproduction:

Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 83,88 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H220 : Extremely flammable gas.

H280 : Contains gas under pressure; may explode if heated.

H304 : May be fatal if swallowed and enters airways.

H317 : May cause an allergic skin reaction.

Full text of other abbreviations

Note C : Some organic substances may be marketed either in a specif-

ic isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the sub-



according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

stance is a specific isomer or a mixture of isomers.

Note L : The classification as a carcinogen need not apply if it can be

shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 %

w/w benzene (Einecs No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260- P262-P301 + P310-P331 shall apply. This note applies only to certain complex oil-derived sub-

stances in Part 3.

Note U (table 3.1) : When put on the market gases have to be classified as "Gas-

es under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part

2, Section 2.3.2.1, Note 2).

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP -Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL -International Convention for the Prevention of Pollution from Ships: n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European

according to Regulation (EC) No. 1907/2006 - DE



OKS 601

VersionRevision Date:Date of last issue: 26.07.2018Print Date:2.229.06.2021Date of first issue: 06.06.201629.06.2021

Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Classification procedure:

Aerosol 1 H222, H229 Based on product data or assessment Asp. Tox. 1 H304 Based on product data or assessment

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.

