

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 571

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Lubricant spray

Recommended restrictions : Restricted to professional users.
on use

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
D-82216 Maisach-Gernlinden
Tel.: +49 8142 3051 500
Fax.: +49 8142 3051 599
info@oks-germany.com

E-mail address of person : mcm@oks-germany.com
responsible for the SDS Material Compliance Management

National contact :

1.4 Emergency telephone number

Emergency telephone num- : +49 8142 3051 517
ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single ex- posure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)






OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters air-ways.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :   

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters air-ways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
Storage:
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

butanone

acetone

xylene

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Active substance with propellant
Solvent
PTFE
Silicone resin

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	921-024-6 01-2119475514-35-XXXX	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411		>= 10 - < 20
butanone	78-93-3 201-159-0 606-002-00-3 01-2119457290-43-XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		>= 1 - < 10
acetone	67-64-1 200-662-2 606-001-00-8	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		>= 1 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version 1.4 Revision Date: 11.07.2022 Date of last issue: 24.07.2018 Print Date: 06.09.2022
Date of first issue: 09.07.2016

	01-2119471330-49-XXXX			
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-21119475103-46-XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		>= 1 - < 10
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32-XXXX	Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315 Eye Irrit.2; H319 STOT SE3; H335 STOT RE2; H373 STOT RE2; H373 Asp. Tox.1; H304	Note C	>= 1 - < 10
Substances with a workplace exposure limit :				
dimethyl ether	115-10-6 204-065-8 603-019-00-8 01-2119472128-37-XXXX	Flam. Gas1A; H220 Press. GasLique- fied gas; H280	Note U (table 3.1)	>= 50 - < 70
Ethylene, tetrafluoro-, polymer	9002-84-0 618-337-2	Not classified		>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Get medical attention immediately if irritation develops and persists.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

Wash clothing before reuse.
Thoroughly clean shoes before reuse.
Wash off immediately with plenty of water.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
Seek medical advice.

If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.
Aspiration hazard if swallowed - can enter lungs and cause damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Skin contact may provoke the following symptoms:
Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Central nervous system depression
Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.
Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire Hazard
Do not let product enter drains.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides
Halogenated compounds
Metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Refer to protective measures listed in sections 7 and 8.
Only qualified personnel equipped with suitable protective equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not use sparking tools.
These safety instructions also apply to empty packaging which may still contain product residues.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
- Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.
- Storage class (TRGS 510) : 2B, Aerosol cans and lighters

7.3 Specific end use(s)

- Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m ³	2000/39/EC (2000-06-16)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version 1.4 Revision Date: 11.07.2022 Date of last issue: 24.07.2018
Date of first issue: 09.07.2016

Print Date:
06.09.2022

	Further information: Indicative			
		AGW	1.000 ppm 1.900 mg/m ³	DE TRGS 900 (2010-08-04)
	Peak-limit: excursion factor (category): 8;(II)			
butanone	78-93-3	TWA	200 ppm 600 mg/m ³	2000/39/EC (2000-06-16)
	Further information: Indicative			
		STEL	300 ppm 900 mg/m ³	2000/39/EC (2000-06-16)
	Further information: Indicative			
		AGW	200 ppm 600 mg/m ³	DE TRGS 900 (2010-08-04)
	Peak-limit: excursion factor (category): 1;(I)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
acetone	67-64-1	TWA	500 ppm 1.210 mg/m ³	2000/39/EC (2000-06-16)
	Further information: Indicative			
		AGW	500 ppm 1.200 mg/m ³	DE TRGS 900 (2015-03-02)
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Ethylene, tetrafluoro-, polymer	9002-84-0	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900 (2020-03-30)
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m ³	DE TRGS 900 (2020-03-30)
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
ethyl acetate	141-78-6	AGW	200 ppm 730 mg/m ³	DE TRGS 900 (2017-06-08)
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		STEL	400 ppm 1.468 mg/m ³	2017/164/EU (2017-02-01)
	Further information: Indicative			
		TWA	200 ppm 734 mg/m ³	2017/164/EU (2017-02-01)
	Further information: Indicative			
xylene	1330-20-7	TWA	50 ppm	2000/39/EC

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version 1.4 Revision Date: 11.07.2022 Date of last issue: 24.07.2018 Date of first issue: 09.07.2016 Print Date: 06.09.2022

			221 mg/m ³	(2000-06-16)
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC (2000-06-16)
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 220 mg/m ³	DE TRGS 900 (2020-10-02)
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Skin absorption			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
butanone	78-93-3	2-butanone: 2 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903 (2015-11-06)
acetone	67-64-1	Acetone: 80 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903 (2004-08-01)
xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903 (2021-01-13)

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
dimethyl ether	Workers	Inhalation	Long-term exposure	1894 mg/m ³
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Workers	Skin contact	Long-term systemic effects	773 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	2035 mg/m ³
butanone	Workers	Inhalation	Long-term systemic effects	600 mg/m ³
	Workers	Skin contact	Long-term systemic effects	1161 mg/kg
xylene	Workers	Inhalation	Long-term exposure, Systemic effects	77 mg/m ³
	Workers	Inhalation	Short-term exposure, Systemic effects	289 mg/m ³
	Workers	Skin contact	Long-term exposure, Systemic effects	180 mg/kg
	Consumers	Inhalation	Long-term exposure, Systemic effects	14,8 mg/m ³
	Consumers	Inhalation	Short-term exposure, Systemic effects	174 mg/m ³
	Consumers	Ingestion	Long-term exposure, Systemic effects	1,6 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version 1.4 Revision Date: 11.07.2022 Date of last issue: 24.07.2018 Print Date: 06.09.2022
Date of first issue: 09.07.2016

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
dimethyl ether	Fresh water	0,155 mg/l
	Marine water	0,016 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water sediment	0,681 mg/kg
	Marine sediment	0,069 mg/kg
butanone	Soil	0,045 mg/kg
	Fresh water	55,8 mg/l
	Marine water	55,8 mg/l
	Intermittent use/release	55,8 mg/l
	Sewage treatment plant	709 mg/l
xylene	Fresh water sediment	284,7 mg/kg
	Marine sediment	284,7 mg/kg
	Soil	22,5 mg/kg
	Fresh water	0,327 mg/l
	Marine water	0,327 mg/l
	Fresh water sediment	12,46 mg/l
	Marine sediment	12,46 mg/l
	Soil	2,31 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : butyl-rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Recommended Filter type:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

Organic gas and low boiling vapour type (AX)

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	aerosol
Colour	:	white
Odour	:	solvent-like
Odour Threshold	:	No data available
Melting point/range	:	No data available
Boiling point/boiling range	:	< -20 °C (1.013 hPa)
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	26,2 %(V)
Lower explosion limit / Lower flammability limit	:	1,4 %(V)
Flash point	:	-20 °C Method: Abel-Pensky
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	< 20,5 mm ² /s (40 °C)
Solubility(ies)	:	
Water solubility	:	insoluble

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 4.400 hPa (20 °C)

Relative density : 0,738 (20 °C)
Reference substance: Water
The value is calculated

Density : 0,74 g/cm³
(20 °C)

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : not auto-flammable

Metal corrosion rate : Not corrosive to metals

Evaporation rate : No data available

Sublimation point : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.
Risk of receptacle bursting.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:
Symptoms: Central nervous system depression

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method
Remarks: Respiration of solvent vapour may cause dizziness.
Symptoms: Inhalation may provoke the following symptoms:,
Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fa-
tigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method
Symptoms: Redness, Local irritation

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg
Assessment: The substance or mixture has no acute oral tox-
icity

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhala-
tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,8 g/kg
Assessment: The substance or mixture has no acute dermal
toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

butanone:

Acute oral toxicity : LD50 (Rat): 2.193 mg/kg
Method: OECD Test Guideline 423
GLP: yes

Acute inhalation toxicity : LC50 (Rat): 34 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402

acetone:

Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

ethyl acetate:

Acute oral toxicity : LD50 (Rat): 5.620 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 20.000 mg/kg

xylene:

Acute oral toxicity : LD50 (Rat): 4.300 mg/kg

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

dimethyl ether:

Acute inhalation toxicity : LC50 (Rat): 309 mg/l
Exposure time: 4 h
Test atmosphere: gas

Ethylene, tetrafluoro-, polymer:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit
Assessment : Irritating to skin.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

Method : OECD Test Guideline 404
Result : Irritating to skin.

butanone:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation

Result : Repeated exposure may cause skin dryness or cracking.

acetone:

Result : Repeated exposure may cause skin dryness or cracking.

ethyl acetate:

Species : Rabbit
Result : Mild skin irritation

Result : Repeated exposure may cause skin dryness or cracking.

xylene:

Species : Rabbit
Assessment : Irritating to skin.
Result : Irritating to skin.

dimethyl ether:

Assessment : No skin irritation
Result : No skin irritation

Ethylene, tetrafluoro-, polymer:

Species : Rabbit
Assessment : No skin irritation
Result : No skin irritation

Serious eye damage/eye irritation

Product:

Remarks : Irritating to eyes.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit
Assessment : No eye irritation
Result : No eye irritation

butanone:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

Species : Rabbit
Assessment : Irritating to eyes.
Method : OECD Test Guideline 405
Result : Irritating to eyes.

acetone:

Species : Rabbit
Result : Eye irritation

ethyl acetate:

Assessment : Irritating to eyes.
Result : Irritating to eyes.

xylene:

Species : Rabbit
Assessment : Irritating to eyes.
Result : Irritating to eyes.

dimethyl ether:

Assessment : No eye irritation
Result : No eye irritation

Ethylene, tetrafluoro-, polymer:

Species : Rabbit
Assessment : No eye irritation
Result : No eye irritation

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Maximisation Test
Exposure routes : Dermal
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Did not cause sensitisation on laboratory animals.

butanone:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

Result : Does not cause skin sensitisation.
GLP : yes

ethyl acetate:

Test Type : Maximisation Test
Exposure routes : Dermal
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

xylene:

Species : Mouse
Assessment : Did not cause sensitisation on laboratory animals.
Method : OECD Test Guideline 429
Result : Did not cause sensitisation on laboratory animals.

dimethyl ether:

Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

Ethylene, tetrafluoro-, polymer:

Assessment : Did not cause sensitisation on laboratory animals.
Result : Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available
Genotoxicity in vivo : Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Test system: Rodent cell line
Method: OECD Test Guideline 473
Result: negative

butanone:

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

xylene:

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

assessment mutagenic effects.

dimethyl ether:

Genotoxicity in vitro : Test Type: Ames test
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Species: Drosophila melanogaster (vinegar fly)
Application Route: inhalation (gas)
Method: OECD Test Guideline 477
Result: negative

Carcinogenicity

Product:

Remarks : No data available

Components:

butanone:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

xylene:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

dimethyl ether:

Species : Rat
Application Route : inhalation (gas)
Exposure time : 2 Years
: 47 mg/l
Method : OECD Test Guideline 453
Result : negative

Ethylene, tetrafluoro-, polymer:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

Components:

butanone:

Reproductive toxicity - Assessment : - Fertility -
No toxicity to reproduction
- Teratogenicity -
No effects on or via lactation

xylene:

Reproductive toxicity - Assessment : - Fertility -
No toxicity to reproduction
- Teratogenicity -
No toxicity to reproduction

dimethyl ether:

Reproductive toxicity - Assessment : - Fertility -
Animal testing did not show any effects on fertility.

STOT - single exposure

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

butanone:

Exposure routes : Inhalation
Target Organs : Respiratory system
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.,
May cause drowsiness or dizziness.

acetone:

Exposure routes : Inhalation
Assessment : May cause drowsiness or dizziness.

ethyl acetate:

Exposure routes : Inhalation
Target Organs : Respiratory system
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

xylene:

Exposure routes : Inhalation
Target Organs : Respiratory system

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

Ethylene, tetrafluoro-, polymer:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Exposure routes : inhalation (vapour)
Assessment : No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

butanone:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

ethyl acetate:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

xylene:

Exposure routes : Inhalation
Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Exposure routes : Ingestion
Target Organs : Liver, Kidney
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Ethylene, tetrafluoro-, polymer:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

butanone:

No aspiration toxicity classification

xylene:

May be fatal if swallowed and enters airways.

dimethyl ether:

No aspiration toxicity classification

Ethylene, tetrafluoro-, polymer:

No aspiration toxicity classification

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

SECTION 12: Ecological information

12.1 Toxicity

Product:

- Toxicity to fish : Remarks: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available
- Toxicity to algae/aquatic plants : Remarks: No data available
- Toxicity to microorganisms : Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 22 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
GLP: yes
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes
- Toxicity to algae/aquatic plants : EbC50 (Pseudokirchneriella subcapitata (green algae)): 26 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Ecotoxicology Assessment

- Acute aquatic toxicity : Toxic to aquatic life.
- Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

butanone:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.993 mg/l
Exposure time: 96 h
Test Type: static test
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 308 mg/l
Exposure time: 48 h
Test Type: static test
- Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): 1.972

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

plants mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

Toxicity to microorganisms : EC50 (*Pseudomonas putida*): 1.150 mg/l
Exposure time: 16 h
Test Type: static test
Method: DIN 38 412 Part 8

ethyl acetate:

Toxicity to fish : LC50 (*Pimephales promelas* (fathead minnow)): 212,5 mg/l
Exposure time: 96 h
Test Type: static test

Toxicity to daphnia and other : EC50 (*Daphnia magna* (Water flea)): 154 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (*Pseudokirchneriella subcapitata* (green algae)): 2.500
plants mg/l
Exposure time: 96 h

xylene:

Toxicity to fish : LC50 (*Oncorhynchus mykiss* (rainbow trout)): 2,6 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (*Daphnia magna* (Water flea)): 3,82 mg/l
aquatic invertebrates Exposure time: 48 h
Test Type: flow-through test

Toxicity to algae/aquatic : EC50 (*Pseudokirchneriella subcapitata* (green algae)): 2,2
plants mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

Toxicity to microorganisms : EC50 (activated sludge): > 157 mg/l
Exposure time: 3 h
Test Type: Respiration inhibition
Method: OECD Test Guideline 209

Toxicity to fish (Chronic tox- : NOEC: > 1,3 mg/l
icity) Exposure time: 56 d
Species: *Oncorhynchus mykiss* (rainbow trout)
Test Type: flow-through test

Toxicity to daphnia and other : EC50: 2,90 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

aquatic invertebrates (Chronic toxicity) : Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: static test
Method: OECD Test Guideline 211
GLP: yes

dimethyl ether:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4.100 mg/l
Exposure time: 96 h
Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 4.400 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae/aquatic plants : EC50 (green algae): 154,9 mg/l
Exposure time: 96 h

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.

butanone:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: rapidly biodegradable
Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
GLP: yes

acetone:

Biodegradability : Result: rapidly biodegradable

ethyl acetate:

Biodegradability : Result: rapidly biodegradable

xylene:

Biodegradability : Result: Readily biodegradable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version 1.4	Revision Date: 11.07.2022	Date of last issue: 24.07.2018 Date of first issue: 09.07.2016	Print Date: 06.09.2022
----------------	------------------------------	---	---------------------------

dimethyl ether:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Components:

butanone:

Bioaccumulation : Remarks: Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

Partition coefficient: n-octanol/water : log Pow: 0,3 (40 °C)
Method: OECD Test Guideline 117
GLP: yes

acetone:

Bioaccumulation : Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 0,2

ethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 0,68 (25 °C)

xylene:

Bioaccumulation : Bioconcentration factor (BCF): 25,9

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15

dimethyl ether:

Partition coefficient: n-octanol/water : log Pow: 0,07 (25 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

butanone:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

xylene:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

dimethyl ether:

Assessment : Non-classified vPvB substance. Non-classified PBT substance

Ethylene, tetrafluoro-, polymer:

Assessment : Non-classified vPvB substance. Non-classified PBT substance

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.
- Waste codes should be assigned by the user based on the application for which the product was used.
- Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.
- The following Waste Codes are only suggestions:
- Waste Code : unused product, packagings not completely emptied
16 05 04*, gases in pressure containers (including halons)
containing hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

- ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

- ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : Aerosols, flammable

14.3 Transport hazard class(es)

- ADN : 2
ADR : 2
RID : 2
IMDG : 2.1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1

ADR

Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

IMDG

Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable
- REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). (EU SVHC) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
- REACH - List of substances subject to authorisation (Annex XIV) (EU. REACH-Annex XIV) : Not applicable
- Regulation (EC) No 1005/2009 on substances that deplete the ozone layer (EC 1005/2009) : Not applicable
- Regulation (EU) 2019/1021 on persistent organic pollutants (recast) (EU POP) : Not applicable
- Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals (EU PIC) : Not applicable
- Regulation (EU) 2019/1148 on the marketing and use of explosives precursors : Listed
- This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see https://ec.europa.eu/home-affairs/sites/homeaffairs/files/what-we-do/policies/crisis-and-terrorism/explosives/explosives-precursors/docs/list_of_competent_authorities_and_national_contact_points_en.pdf acetone (ANNEX II)

: P2

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

P5c

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P3a FLAMMABLE AEROSOLS

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : Total dust:
others: 3,62 %

Inorganic substances in powdered form:
Not applicable
Inorganic substances in vapour or gaseous form:
Not applicable
Organic Substances:
portion Class 1: 0,05 %
others: 89,08 %

Carcinogenic substances:
Not applicable
Mutagenic:
Not applicable
Toxic to reproduction:
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 92,93 %

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

EUH066 : Repeated exposure may cause skin dryness or cracking.
H220 : Extremely flammable gas.
H225 : Highly flammable liquid and vapour.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

- H226 : Flammable liquid and vapour.
- H280 : Contains gas under pressure; may explode if heated.
- H304 : May be fatal if swallowed and enters airways.
- H312 : Harmful in contact with skin.
- H315 : Causes skin irritation.
- H319 : Causes serious eye irritation.
- H332 : Harmful if inhaled.
- H335 : May cause respiratory irritation.
- H336 : May cause drowsiness or dizziness.
- H373 : May cause damage to organs through prolonged or repeated exposure if inhaled.
- H373 : May cause damage to organs through prolonged or repeated exposure if swallowed.
- H411 : Toxic to aquatic life with long lasting effects.
- EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

- Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- Note U (table 3.1) : When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).
- 2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
- 2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
- DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
- TRGS 903 : TRGS 903 - Biological limit values
- 2000/39/EC / TWA : Limit Value - eight hours
- 2000/39/EC / STEL : Short term exposure limit
- 2017/164/EU / STEL : Short term exposure limit
- 2017/164/EU / TWA : Limit Value - eight hours
- DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regula-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

tion (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Based on product data or assessment
Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE
(Commission Regulation (EU) 2020/878)



OKS 571

Version	Revision Date:	Date of last issue: 24.07.2018	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	06.09.2022

product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.