



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 25

Pattex Kraftkleber Classic

SDS No. : 390436

V005.1

Revision: 07.04.2022

printing date: 03.08.2022

Replaces version from: 16.07.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Pattex Kraftkleber Classic

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Contact adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

ua-productsafety.uk@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids	Category 2
H225 Highly flammable liquid and vapor.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

Ethylacetate

Methylcyclohexane

Signal word:

Danger

Hazard statement:

H225 Highly flammable liquid and vapor.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Supplemental information

Contains: rosin May produce an allergic reaction.

Precautionary statement:

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.

**Precautionary statement:
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
 No smoking.
 P261 Avoid breathing mist/vapours.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/eye protection.

**Precautionary statement:
Storage**

P403 Store in a well-ventilated place.

**Precautionary statement:
Disposal**

P501 Dispose of contents/container in accordance with national regulation.

2.3. Other hazards

Solvents contained in the product evaporate during processing and their vapors can form explosive/highly inflammable air/vapor mixtures.

Pregnant women should absolutely avoid inhalation and skin contact.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration $\geq 0,1\%$ and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration \geq the concentration limit that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Ethyl acetate 141-78-6 205-500-4 01-2119475103-46	20- 40 %	Flam. Liq. 2, H225 STOT SE 3, H336 Eye Irrit. 2, H319		EU OEL
Methylcyclohexane 108-87-2 203-624-3	25- 40 %	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n- hexane 92128-66-0 926-605-8 01-2119486291-36	5- < 10 %	Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n- hexane 92128-66-0 921-024-6 01-2119475514-35	1- < 5 %	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411		
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0 927-510-4 01-2119475515-33	1- < 5 %	Asp. Tox. 1, H304 Skin Irrit. 2, H315 Flam. Liq. 2, H225 STOT SE 3, Inhalation, H336 Aquatic Chronic 2, H411	inhalation:ATE= 23,31 mg/l;	
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0 265-151-9	1- < 5 %	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411		
zinc oxide 1314-13-2 215-222-5 01-2119463881-32	0,1- < 1 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
rosin 8050-09-7 232-475-7 01-2119480418-32	0,1- < 1 %	Skin Sens. 1, H317		
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5 271-867-2 01-2119496062-39	0,1- < 1 %	Repr. 2, H361d Aquatic Chronic 4, H413		

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

SKIN: Redness, inflammation.

Vapors may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Fire fighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO₂) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

Additional information:

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Danger of slipping on spilled product.

Ensure adequate ventilation.

Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ventilate working rooms thoroughly. Avoid naked flames, sparking and sources of ignition. Switch off electrical devices. Do not smoke, do not weld. Do not empty waste into waste water drains.

During processing and drying after adhesion, ventilate well. Avoid all sources of fire such as stoves and ovens. Switch off all electrical devices such as parabolic heaters, hot plates, storage heaters etc. in good time for them to have cooled down before commencing work. Avoid all sparks, including those occurring at electrical switches and devices.

Avoid skin and eye contact.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Keep only in original container.

Close the container carefully after use and store it at a good ventilated place.

Avoid strictly temperatures below +5 °C and above +50 °C.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Contact adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethyl acetate 141-78-6 [ETHYL ACETATE]	200	734	Time Weighted Average (TWA):	Indicative	ECLTV
Ethyl acetate 141-78-6 [ETHYL ACETATE]	400	1.468	Short Term Exposure Limit (STEL):	Indicative	ECLTV
Ethyl acetate 141-78-6 [ETHYL ACETATE]	200	734	Time Weighted Average (TWA):		EH40 WEL
Ethyl acetate 141-78-6 [ETHYL ACETATE]	400	1.468	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Rosin 8050-09-7 [ROSIN-BASED SOLDER FLUX FUME]		0,05	Time Weighted Average (TWA):		EH40 WEL
Rosin 8050-09-7 [ROSIN-BASED SOLDER FLUX FUME]		0,15	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Zinc oxide 1314-13-2 [Dust, inhalable dust]		10	Time Weighted Average (TWA):		EH40 WEL
Zinc oxide 1314-13-2 [Dust, respirable dust]		4	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethyl acetate 141-78-6 [ETHYL ACETATE]	200	734	Time Weighted Average (TWA):	Indicative	ECLTV
Ethyl acetate 141-78-6 [ETHYL ACETATE]	400	1.468	Short Term Exposure Limit (STEL):	Indicative	ECLTV
Ethyl acetate 141-78-6 [ETHYL ACETATE]	200	734	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Ethyl acetate 141-78-6 [ETHYL ACETATE]	400	1.468	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
Methylcyclohexane 108-87-2 [METHYLCYCLOHEXANE]	400	1.600	Time Weighted Average (TWA):		IR_OEL
Resin acids and Rosin acids, hydrogenated, esters with glycerol 65997-13-9 [ROSIN CORE SOLDER PYROLYSIS PRODUCTS]		0,15	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
Resin acids and Rosin acids, hydrogenated, esters with glycerol 65997-13-9 [ROSIN CORE SOLDER PYROLYSIS PRODUCTS]		0,05	Time Weighted Average (TWA):		IR_OEL
Rosin 8050-09-7 [ROSIN CORE SOLDER PYROLYSIS PRODUCTS]		0,05	Time Weighted Average (TWA):		IR_OEL
Rosin		0,15	Short Term Exposure	15 minutes	IR_OEL

8050-09-7 [ROSIN CORE SOLDER PYROLYSIS PRODUCTS]			Limit (STEL):		
Zinc oxide 1314-13-2 [ZINC OXIDE,]		2	Time Weighted Average (TWA):		IR_OEL
Zinc oxide 1314-13-2 [ZINC OXIDE,]		10	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
Disulfiram 97-77-8 [DISULFIRAM]		2	Time Weighted Average (TWA):		IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Ethyl acetate 141-78-6	aqua (freshwater)		0,24 mg/l				
Ethyl acetate 141-78-6	aqua (marine water)		0,024 mg/l				
Ethyl acetate 141-78-6	aqua (intermittent releases)		1,65 mg/l				
Ethyl acetate 141-78-6	sewage treatment plant (STP)		650 mg/l				
Ethyl acetate 141-78-6	sediment (freshwater)				1,15 mg/kg		
Ethyl acetate 141-78-6	sediment (marine water)				0,115 mg/kg		
Ethyl acetate 141-78-6	Air						no hazard identified
Ethyl acetate 141-78-6	Soil				0,148 mg/kg		
Ethyl acetate 141-78-6	oral				200 mg/kg		
zinc oxide 1314-13-2	aqua (freshwater)		0,0206 mg/l				
zinc oxide 1314-13-2	aqua (marine water)		0,0061 mg/l				
zinc oxide 1314-13-2	sewage treatment plant (STP)		0,1 mg/l				
zinc oxide 1314-13-2	sediment (freshwater)				117,8 mg/kg		
zinc oxide 1314-13-2	sediment (marine water)				56,5 mg/kg		
zinc oxide 1314-13-2	Soil				35,6 mg/kg		
zinc oxide 1314-13-2	Air						no hazard identified
zinc oxide 1314-13-2	oral						no potential for bioaccumulation
rosin 8050-09-7	aqua (freshwater)		0,002 mg/l				
rosin 8050-09-7	aqua (marine water)		0,0002 mg/l				
rosin 8050-09-7	sediment (freshwater)				0,007 mg/kg		
rosin 8050-09-7	sediment (marine water)				0,001 mg/kg		
rosin 8050-09-7	Soil				0 mg/kg		
rosin 8050-09-7	sewage treatment plant (STP)		1000 mg/l				
rosin 8050-09-7	aqua (intermittent releases)		0,016 mg/l				
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	aqua (freshwater)		0,01 mg/l				
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	aqua (marine water)		0,002 mg/l				
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	sewage treatment plant (STP)		100 mg/l				
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	sediment (freshwater)				426,26 mg/kg		
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	sediment (marine water)				85,25 mg/kg		
Phenol, 4-methyl-, reaction products with	Soil				85,16		

dicyclopentadiene and isobutylene 68610-51-5					mg/kg		
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	oral				1,7 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Ethyl acetate 141-78-6	Workers	inhalation	Acute/short term exposure - systemic effects		1468 mg/m3	no hazard identified
Ethyl acetate 141-78-6	Workers	inhalation	Acute/short term exposure - local effects		1468 mg/m3	no hazard identified
Ethyl acetate 141-78-6	Workers	dermal	Long term exposure - systemic effects		63 mg/kg	no hazard identified
Ethyl acetate 141-78-6	Workers	inhalation	Long term exposure - systemic effects		734 mg/m3	no hazard identified
Ethyl acetate 141-78-6	Workers	inhalation	Long term exposure - local effects		734 mg/m3	no hazard identified
Ethyl acetate 141-78-6	General population	Inhalation	Acute/short term exposure - systemic effects		734 mg/m3	no hazard identified
Ethyl acetate 141-78-6	General population	inhalation	Acute/short term exposure - local effects		734 mg/m3	no hazard identified
Ethyl acetate 141-78-6	General population	dermal	Long term exposure - systemic effects		37 mg/kg	no hazard identified
Ethyl acetate 141-78-6	General population	inhalation	Long term exposure - systemic effects		367 mg/m3	no hazard identified
Ethyl acetate 141-78-6	General population	oral	Long term exposure - systemic effects		4,5 mg/kg	no hazard identified
Ethyl acetate 141-78-6	General population	inhalation	Long term exposure - local effects		367 mg/m3	no hazard identified
Methylcyclohexane 108-87-2	Workers	dermal	Long term exposure - systemic effects		773 mg/kg	
Methylcyclohexane 108-87-2	Workers	Inhalation	Long term exposure - systemic effects		2035 mg/m3	
Methylcyclohexane 108-87-2	General population	dermal	Long term exposure - systemic effects		699 mg/kg	
Methylcyclohexane 108-87-2	General population	Inhalation	Long term exposure - systemic effects		608 mg/m3	
Methylcyclohexane 108-87-2	General population	oral	Long term exposure - systemic effects		699 mg/kg	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Workers	dermal	Long term exposure - systemic effects		13964 mg/kg	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Workers	inhalation	Long term exposure - systemic effects		5306 mg/m3	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	General population	dermal	Long term exposure - systemic effects		1377 mg/kg	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	General population	inhalation	Long term exposure - systemic effects		1131 mg/m3	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	General population	oral	Long term exposure - systemic effects		1301 mg/kg	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Workers	dermal	Long term exposure - systemic effects		773 mg/kg	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Workers	inhalation	Long term exposure - systemic effects		2035 mg/m3	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	General population	dermal	Long term exposure -		699 mg/kg	

92128-66-0			systemic effects			
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	General population	inhalation	Long term exposure - systemic effects		608 mg/m ³	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	General population	oral	Long term exposure - systemic effects		699 mg/kg	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Workers	dermal	Long term exposure - systemic effects		300 mg/kg	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Workers	inhalation	Long term exposure - systemic effects		2085 mg/m ³	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	General population	dermal	Long term exposure - systemic effects		149 mg/kg	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	General population	oral	Long term exposure - systemic effects		149 mg/kg	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	General population	inhalation	Long term exposure - systemic effects		447 mg/m ³	
zinc oxide 1314-13-2	Workers	Inhalation	Long term exposure - systemic effects		5 mg/m ³	no hazard identified
zinc oxide 1314-13-2	Workers	dermal	Long term exposure - systemic effects		83 mg/kg	no hazard identified
zinc oxide 1314-13-2	Workers	inhalation	Long term exposure - local effects		0,5 mg/m ³	no hazard identified
zinc oxide 1314-13-2	General population	Inhalation	Long term exposure - systemic effects		2,5 mg/m ³	no hazard identified
zinc oxide 1314-13-2	General population	dermal	Long term exposure - systemic effects		83 mg/kg	no hazard identified
zinc oxide 1314-13-2	General population	oral	Long term exposure - systemic effects		0,83 mg/kg	no hazard identified
rosin 8050-09-7	Workers	inhalation	Long term exposure - local effects		10 mg/m ³	
rosin 8050-09-7	Workers	dermal	Long term exposure - systemic effects		2,131 mg/kg	
rosin 8050-09-7	General population	dermal	Long term exposure - systemic effects		1,065 mg/kg	
rosin 8050-09-7	General population	oral	Long term exposure - systemic effects		1,065 mg/kg	
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	Workers	dermal	Long term exposure - systemic effects		0,42 mg/kg	
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	Workers	inhalation	Long term exposure - systemic effects		0,29 mg/m ³	
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	General population	dermal	Long term exposure - systemic effects		0,21 mg/kg	
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	General population	inhalation	Long term exposure - systemic effects		0,07 mg/m ³	
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	General population	oral	Long term exposure - systemic effects		0,04 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.

Combination filter: ABEKP (EN 14387)

This recommendation should be matched to local conditions.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s).Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374.

Perforation time > 10 minutes

material thickness > 0.4 mm

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Delivery form	liquid
Colour	beige
Odor	Solvent
Initial boiling point	75 °C (167 °F)no method
Explosive limits	
lower	1,4 %(V); No data available.
upper	8,60 %(V); No data available.
Flash point	< -10 °C (< 14 °F); DIN EN ISO 3679
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic) (20 °C (68 °F);)	> 1.000 mm ² /s ;no method
Viscosity, dynamic (Brookfield; 20 °C (68 °F); speed of rotation: 50 min ⁻¹ ; Spindle No: 4)	1.700 - 2.300 cp TE1002-208; Viscosity by Brookfield
Solubility (qualitative) (23 °C (73.4 °F); Solvent: Water)	Partially soluble
Vapour pressure (20 °C (68 °F))	120 mbar
Vapour pressure (25 °C (77 °F))	150 mbar
Vapour pressure (50 °C (122 °F))	430 mbar
Vapour pressure (70 °C (158 °F))	860 mbar
Density (20 °C (68 °F))	0,84 - 0,88 g/ml QP2107.1; Density

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity**10.1. Reactivity**

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information**General toxicological information:**

An allergic reaction cannot be excluded after repeated skin contact.

Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Ethyl acetate 141-78-6	LD50	6.100 mg/kg	rat	not specified
Methylcyclohexane 108-87-2	LD50	> 3.200 mg/kg	rat	not specified
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics 64742-49-0	LD50	> 5.840 mg/kg	rat	not specified
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
zinc oxide 1314-13-2	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
rosin 8050-09-7	LD50	2.800 mg/kg	rat	not specified
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Ethyl acetate 141-78-6	LD50	> 20.000 mg/kg	rabbit	Draize Test
Methylcyclohexane 108-87-2	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics 64742-49-0	LD50	> 2.800 mg/kg	rat	other guideline:
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	LD50	> 2.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
zinc oxide 1314-13-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
rosin 8050-09-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The toxicity of the product is due to its narcotic effect after inhalation.

In the event of protracted or repeated exposure, damage to health cannot be excluded.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Ethyl acetate 141-78-6	LC0	> 22,5 mg/l	dust/mist	6 h	rat	other guideline:
Ethyl acetate 141-78-6	LC50	> 22,5 mg/l	dust/mist	6 h	rat	other guideline:
Methylcyclohexane 108-87-2	LC50	> 26,3 mg/l	vapour	1 h	rat	not specified
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	LC50	> 25,2 mg/l	vapour	4 h	rat	not specified
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	LC50	> 23,3 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Acute toxicity estimate (ATE)	23,31 mg/l				Expert judgement
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	LC50	> 5,61 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
zinc oxide 1314-13-2	LC50	> 5,7 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	LC50	> 165 mg/l	dust/mist	4 h	rat	not specified

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Ethyl acetate 141-78-6	slightly irritating	24 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Methylcyclohexane 108-87-2	not irritating	24 h	rabbit	Draize Test
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
zinc oxide 1314-13-2	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
rosin 8050-09-7	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	not irritating	4 h	rabbit	EPA Guideline

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Ethyl acetate 141-78-6	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Methylcyclohexane 108-87-2	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics 64742-49-0	not irritating		rabbit	FDA Guideline
zinc oxide 1314-13-2	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
rosin 8050-09-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	slightly irritating	24 h	rabbit	EPA Guideline

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Ethyl acetate 141-78-6	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Methylcyclohexane 108-87-2	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics 64742-49-0	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
zinc oxide 1314-13-2	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study/ Route of administration	Metabolic activation/ Exposure time	Species	Method
Ethyl acetate 141-78-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Ethyl acetate 141-78-6	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Methylcyclohexane 108-87-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Methylcyclohexane 108-87-2	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Methylcyclohexane 108-87-2	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
zinc oxide 1314-13-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
zinc oxide 1314-13-2	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
zinc oxide 1314-13-2	ambiguous	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
rosin 8050-09-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Ethyl acetate 141-78-6	negative	oral: gavage		hamster, Chinese	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
zinc oxide 1314-13-2	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
zinc oxide 1314-13-2	not carcinogenic	oral: drinking water	1 y daily	mouse	male/female	not specified

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Ethyl acetate 141-78-6	NOAEL P 1500 ppm	other:	inhalation	rat	other guideline:
Methylcyclohexane 108-87-2	NOAEL P 250 mg/kg NOAEL F1 1.000 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
zinc oxide 1314-13-2	NOAEL P 7,5 mg/kg NOAEL F1 15 mg/kg	Two generation study	oral: gavage	rat	equivalent or similar to OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Ethyl acetate 141-78-6	NOAEL 900 mg/kg	oral: gavage	90 d daily	rat	EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
Methylcyclohexane 108-87-2	NOAEL 250 mg/kg	oral: gavage	28 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
zinc oxide 1314-13-2	NOAEL 31,52 mg/kg	oral: feed	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
zinc oxide 1314-13-2	NOAEL 1.5 mg/m ³	inhalation	3 m 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	NOAEL 500 ppm	oral: feed	90 Days Daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	0,5 mm ² /s	20 °C	not specified	

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl acetate 141-78-6	LC50	220 mg/l	96 h	Pimephales promelas	other guideline:
Methylcyclohexane 108-87-2	LC50	2,07 mg/l	96 h	Oryzias latipes	other guideline:
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n- hexane 92128-66-0	LL50	12 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	LL50	11,4 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	LL50	8,2 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
zinc oxide 1314-13-2	LC50	0,142 mg/l	96 h	Thymallus arcticus	OECD Guideline 203 (Fish, Acute Toxicity Test)
zinc oxide 1314-13-2	NOEC	0,44 mg/l	72 d	Oncorhynchus mykiss	other guideline:
rosin 8050-09-7	LC50	Toxicity > Water solubility	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	LC50	Toxicity > Water solubility	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	NOELR	Toxicity > Water solubility	34 d	Pimephales promelas	OECD Guideline 210 (fish early lite stage toxicity test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl acetate 141-78-6	EC50	164 mg/l	48 h	Daphnia cucullata	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Methylcyclohexane 108-87-2	EC50	0,326 mg/l	48 h	Daphnia magna	other guideline:
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n- hexane 92128-66-0	EL50	3 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	EL50	3 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	EC50	3 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	EL50	4,5 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
zinc oxide 1314-13-2	EC50	1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
rosin	EL50	Toxicity > Water	48 h	Daphnia magna	OECD Guideline 202

8050-09-7		solubility			(Daphnia sp. Acute Immobilisation Test)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl acetate 141-78-6	NOEC	2,4 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	NOEC	0,17 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	NOEC	0,17 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	NOELR	2,6 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
zinc oxide 1314-13-2	NOEC	0,058 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	NOELR	Toxicity > Water solubility	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl acetate 141-78-6	EC50	> 2.000 mg/l	96 h	Selenastrum capricomutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethyl acetate 141-78-6	NOEC	2.000 mg/l	96 h	Selenastrum capricomutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methylcyclohexane 108-87-2	EC50	0,134 mg/l	72 h	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)	other guideline:
Methylcyclohexane 108-87-2	NOEC	0,022 mg/l	72 h	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)	other guideline:
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n- hexane 92128-66-0	EL50	55 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n- hexane 92128-66-0	NOEL	30 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	EL50	> 30 - 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	NOELR	3 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	EL50	29 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	NOELR	6,3 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	EL50	3,1 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	NOELR	0,5 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
zinc oxide 1314-13-2	NOEC	0,017 mg/l	72 h	Selenastrum capricomutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
zinc oxide 1314-13-2	EC50	0,17 mg/l	72 h	Selenastrum capricomutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
rosin 8050-09-7	EL50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
rosin 8050-09-7	NOELR	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	NOEC	Toxicity > Water solubility	72 h	Selenastrum capricomutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	EC50	Toxicity > Water solubility	72 h	Selenastrum capricomutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl acetate 141-78-6	EC10	2.900 mg/l	18 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
zinc oxide	IC50	5,2 mg/l	3 h	not specified	OECD Guideline 209

1314-13-2					(Activated Sludge, Respiration Inhibition Test)
rosin 8050-09-7	EC20	Toxicity > Water solubility	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Ethyl acetate 141-78-6	readily biodegradable	aerobic	100 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Methylcyclohexane 108-87-2	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	readily biodegradable	aerobic	98 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	readily biodegradable	aerobic	98 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	readily biodegradable	aerobic	98 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	readily biodegradable	aerobic	77,05 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
rosin 8050-09-7	readily biodegradable	aerobic	71 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	not inherently biodegradable	aerobic	1 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Ethyl acetate 141-78-6	30	3 d	22,5 °C	Leuciscus idus melanotus	other guideline:
Methylcyclohexane 108-87-2	> 95 - <321	56 day	25 °C	Cyprinus carpio	other guideline:

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Ethyl acetate 141-78-6	0,68	25 °C	EPA OPPTS 830.7560 (Partition Coefficient, n-octanol / H ₂ O, Generator Column Method)
Methylcyclohexane 108-87-2	3,88		other guideline:
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n- hexane 92128-66-0	3,6	20 °C	other guideline:
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	4 - 5,7		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
rosin 8050-09-7	> 3 - 6,2		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	7,56	30 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT/ vPvB
Ethyl acetate 141-78-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
zinc oxide 1314-13-2	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
rosin 8050-09-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

080409

SECTION 14: Transport information
--

14.1. UN number

ADR	1133
RID	1133
ADN	1133
IMDG	1133
IATA	1133

14.2. UN proper shipping name

ADR	ADHESIVES
RID	ADHESIVES
ADN	ADHESIVES
IMDG	ADHESIVES (Methylcyclohexane)
IATA	Adhesives

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packing group

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	Special provision 640D Tunnelcode: (D/E)
RID	Special provision 640D
ADN	Special provision 640D
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

No information available:

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapor.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H361d Suspected of damaging the unborn child.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H413 May cause long lasting harmful effects to aquatic life.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2:	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,
 Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.

Annex - Exposure Scenarios:

Exposure Scenarios for ethyl acetate can be downloaded under the following link:
<https://mysds.henkel.com/index.html#/appSelection>