

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : HP 500 Aktivreiniger (041120330000-0201)
200 L

Revision date : 16.04.2019

Version (Revision) : 21.0.0 (20.0.1)

Print date : 27.04.2020

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

HP 500 Aktivreiniger
200 L

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Products Category [PC]

PC 35 - Washing and cleaning products

1.3 Details of the supplier of the safety data sheet

Supplier : Chemische Werke Kluthe
Werk Oberhausen

Street : Feldstraße 55

Postal code/city : D 46149 Oberhausen

Telephone : +49208 / 9948-166

Telefax : +49208 / 9948-151

Information contact : sds.ob@kluthe.com

1.4 Emergency telephone number

+49177 / 2144737 (24 h)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Exclamation mark (GHS07)

Signal word

Warning

Hazard statements

H319 Causes serious eye irritation.

Precautionary statements

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P337+P313 If eye irritation persists: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : HP 500 Aktivreiniger (041120330000-0201)
200 L

Revision date : 16.04.2019

Version (Revision) : 21.0.0 (20.0.1)

Print date : 27.04.2020

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

AQUEOUS MILD ALKALINE SOLUTION, SURFACTANTS, ADDITIVES

3.2 Mixtures

Hazardous ingredients

1-METHOXY-2-PROPANOL ; REACH No. : 01-2119457435-35 ; EC No. : 203-539-1; CAS No. : 107-98-2

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336

POLY(OXY-1,2-ETHANDIYL).ALPHA.-TRIDECYL-OMEGA.-HDROXY-, BRANCHED ; EC No. : 931-138-8; CAS No. : 69011-36-5

Weight fraction : $\geq 1 - < 3 \%$

Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H302

1-PROPOXY-2-PROPANOL ; REACH No. : 01-2119474443-37 ; EC No. : 216-372-4; CAS No. : 1569-01-3

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH

None

This mixture contains the following substances of very high concern (SVHC) which are subject to authorisation according to Annex XIV of REACH

None

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove affected person from the danger area and lay down. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of respiratory tract irritation, consult a physician.

In case of skin contact

Change contaminated, saturated clothing. Subsequently wash off with: Water and soap

After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Let water be drunken in little sips (dilution effect).

4.2 Most important symptoms and effects, both acute and delayed

Dizziness Headache Impairment of vision Nausea Vomiting

4.3 Indication of any immediate medical attention and special treatment needed

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : HP 500 Aktivreiniger (041120330000-0201)
200 L

Revision date : 16.04.2019

Print date : 27.04.2020

Version (Revision) : 21.0.0 (20.0.1)

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

Co-ordinate fire-fighting measures to the fire surroundings.

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam Carbon dioxide (CO₂) Extinguishing powder Water spray jet

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Protective clothing.

5.4 Additional information

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Provide adequate ventilation. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Use water spray jet to minimise or disperse vapours.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Clear contaminated areas thoroughly.

6.4 Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13 National regulations see section 15.

SECTION 7: Handling and storage



7.1 Precautions for safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Protective measures

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists

Measures to prevent fire

Usual measures for fire prevention. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : HP 500 Aktivreiniger (041120330000-0201)
200 L

Revision date : 16.04.2019

Version (Revision) : 21.0.0 (20.0.1)

Print date : 27.04.2020

Measures to prevent aerosol and dust generation

Vapours/aerosols should be exhausted directly at the point of origin. Use only in well-ventilated areas.

Environmental precautions

Shafts and sewers must be protected from entry of the product.

7.2 Conditions for safe storage, including any incompatibilities

Hints on joint storage

Storage class (TRGS 510) : 12

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 100 ppm / 370 mg/m³

Peak limitation : 2(I)

Remark : Y

Version : 29.03.2019

Limit value type (country of origin) : STEL (EC)

Limit value : 150 ppm / 568 mg/m³

Remark : Skin

Version : 20.06.2019

Limit value type (country of origin) : TWA (EC)

Limit value : 100 ppm / 375 mg/m³

Remark : Skin

Version : 20.06.2019

Biological limit values

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2

Limit value type (country of origin) : TRGS 903 (D)

Parameter : 1-methoxy-2-propanol / Urine (U) / End of exposure or end of shift

Limit value : 15 mg/l

Version : 29.03.2019

DNEL-/PNEC-values

DNEL/DMEL

Limit value type : DNEL Consumer (systemic) (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 18,1 mg/kg

Limit value type : DNEL Consumer (systemic) (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 43,9 mg/m³

Limit value type : DNEL Consumer (systemic) (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)

Exposure route : Oral

Exposure frequency : Long-term

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Harmony in
Chemistry

Trade name : HP 500 Aktivreiniger (041120330000-0201)
200 L

Revision date : 16.04.2019

Version (Revision) : 21.0.0 (20.0.1)

Print date : 27.04.2020

Limit value :	3,3 mg/kg
Limit value type :	DNEL worker (local) (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route :	Inhalation
Exposure frequency :	Short-term
Limit value :	553,5 mg/m ³
Limit value type :	DNEL worker (systemic) (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	50,6 mg/kg
Limit value type :	DNEL worker (systemic) (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	369 mg/m ³
Limit value type :	DNEL Consumer (systemic) (1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3)
Exposure route :	Oral
Exposure frequency :	Long-term
Limit value :	2,2 mg/kg
Limit value type :	DNEL Consumer (systemic) (1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	2,2 mg/kg
Limit value type :	DNEL Consumer (systemic) (1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	26 mg/m ³
Limit value type :	DNEL worker (systemic) (1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	9 mg/kg
Limit value type :	DNEL worker (systemic) (1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	217 mg/m ³
PNEC	
Limit value type :	PNEC (Aquatic, freshwater) (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Limit value :	10 mg/l
Limit value type :	PNEC (Aquatic, marine water) (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Limit value :	1 mg/l
Limit value type :	PNEC (Sediment, freshwater) (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Limit value :	41,6 mg/kg
Limit value type :	PNEC (Sediment, marine water) (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Limit value :	4,17 mg/kg
Limit value type :	PNEC (Soil) (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Limit value :	2,47 mg/kg
Limit value type :	PNEC (Sewage treatment plant) (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Limit value :	100 mg/l
Limit value type :	PNEC (Aquatic, freshwater) (1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3)
Limit value :	0,1 mg/l
Limit value type :	PNEC (Aquatic, intermittent release) (1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3)
Limit value :	1 mg/l

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : HP 500 Aktivreiniger (041120330000-0201)
200 L

Revision date : 16.04.2019

Version (Revision) : 21.0.0 (20.0.1)

Print date : 27.04.2020

Limit value type :	PNEC (Aquatic, marine water) (1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3)
Limit value :	0,01 mg/l
Limit value type :	PNEC (Sediment, freshwater) (1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3)
Limit value :	0,386 mg/kg
Limit value type :	PNEC (Sediment, marine water) (1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3)
Limit value :	0,0386 mg/kg
Limit value type :	PNEC (Soil) (1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3)
Limit value :	0,0185 mg/kg
Limit value type :	PNEC (Sewage treatment plant) (1-PROPOXY-2-PROPANOL ; CAS No. : 1569-01-3)
Limit value :	4 mg/l

8.2 Exposure controls



Personal protection equipment

Eye/face protection

Eye glasses with side protection

Skin protection

Hand protection

Suitable gloves type : Gloves with long cuffs

Suitable material : Butyl caoutchouc (butyl rubber)

Breakthrough time : >= 480 min

Thickness of the glove material : 0,5 mm

Recommended glove articles : EN ISO 374

Additional hand protection measures : Check leak tightness/impermeability prior to use. Do not wear gloves near rotary machines and tools. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Remark : The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Body protection

lab coat Overall Chemical resistant safety shoes Only wear fitting, comfortable and clean protective clothing.

Recommended material : Natural fibres (e.g. cotton) heat-resistant synthetic fibres

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Respiratory protection necessary at: exceeding exposure limit values / aerosol or mist formation.

Suitable respiratory protection apparatus

Filtering device (full mask or mouthpiece) with filter : A-P2

General information

Wash hands before breaks and after work. Apply skin care products after work.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Harmony in
Chemistry

Trade name : HP 500 Aktivreiniger (041120330000-0201)
200 L

Revision date : 16.04.2019

Version (Revision) : 21.0.0 (20.0.1)

Print date : 27.04.2020

Colour : light yellow
Odour : characteristic

Safety characteristics

Melting point/freezing point :			not determined
Initial boiling point and boiling range :	(1013 hPa)	>	100,0 °C
Decomposition temperature :			No data available
Flash point :			none DIN 51755 part 1
Auto-ignition temperature :			none
Oxidising liquids :			Not applicable.
Lower explosion limit :			none
Upper explosion limit :			none
Explosive properties :			Not applicable.
Vapour pressure 20°C):	(20 °C)		No data available
Density :	(20 °C)	approx.	1,090 g/cm ³
Water solubility :	(20 °C)		miscible
pH-value:	(20 °C / conc.)		10,7 - 10,9
pH-value:	(20 °C / 10 g/l)		7,3 - 7,9
log P O/W :			No data available
Cinematic viscosity :	(40 °C)		No data available
Odour threshold :			No data available
Vapourisation rate :			No data available (Ether = 1)
Maximum VOC content (EC) :	(20 °C)		6,0 Wt % gem. RL 2010/75/EG
Max. VOC content (Decopaint):	(20 °C)		9,1 Wt % gem. RL 2004/42/EG

9.2 Other information

no more data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Stable under recommended storage and handling conditions(See section 7).

10.3 Possibility of hazardous reactions

None

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

None

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Harmony in
Chemistry

Trade name : HP 500 Aktivreiniger (041120330000-0201)
200 L

Revision date : 16.04.2019

Version (Revision) : 21.0.0 (20.0.1)

Print date : 27.04.2020

Acute oral toxicity

Parameter :	LD50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route :	Oral
Species :	Rat
Effective dose :	4016 mg/kg
Parameter :	LD50 (POLY(OXY-1,2-ETHANDIYL).ALPHA.-TRIDECYL-.OMEGA.-HDROXY-, BRANCHED ; CAS No. : 69011-36-5)
Exposure route :	Oral
Species :	Rat
Effective dose :	> 200 - 2000 mg/kg
Method :	OECD 423

Acute dermal toxicity

Parameter :	LD50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	2000 mg/kg
Parameter :	LD50 (POLY(OXY-1,2-ETHANDIYL).ALPHA.-TRIDECYL-.OMEGA.-HDROXY-, BRANCHED ; CAS No. : 69011-36-5)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 2000 mg/kg
Method :	OECD 402

Acute inhalation toxicity

Parameter :	LC50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route :	Inhalation
Species :	Rat
Effective dose :	27,596 mg/l
Exposure time :	6 h

Corrosion

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : HP 500 Aktivreiniger (041120330000-0201)
200 L

Revision date : 16.04.2019

Version (Revision) : 21.0.0 (20.0.1)

Print date : 27.04.2020

11.2 Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

11.3 Symptoms related to the physical, chemical and toxicological characteristics

There are no data available on the preparation/mixture itself.

11.4 Other adverse effects

No information available.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Based on available data, the classification criteria are not met.

Acute (short-term) fish toxicity

Parameter :	LC50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Species :	Leuciscus idus (golden orfe)
Effective dose :	6812 mg/l
Exposure time :	96 h
Parameter :	LC50 (POLY(OXY-1,2-ETHANDIYL).ALPHA.-TRIDECYL-.OMEGA.-HDROXY-, BRANCHED ; CAS No. : 69011-36-5)
Species :	Cyprinus carpio (Common Carp)
Effective dose :	> 1 mg/l
Exposure time :	96 h
Method :	OECD 203

Acute (short-term) toxicity to crustacea

Parameter :	EC50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Species :	Daphnia magna (Big water flea)
Effective dose :	23300 mg/l
Exposure time :	48 h
Parameter :	EC50 (POLY(OXY-1,2-ETHANDIYL).ALPHA.-TRIDECYL-.OMEGA.-HDROXY-, BRANCHED ; CAS No. : 69011-36-5)
Species :	Daphnia magna (Big water flea)
Effective dose :	> 1 - 10 mg/l
Exposure time :	48 h
Method :	OECD 202

Chronic (long-term) toxicity to crustacea

Parameter :	EC10 (POLY(OXY-1,2-ETHANDIYL).ALPHA.-TRIDECYL-.OMEGA.-HDROXY-, BRANCHED ; CAS No. : 69011-36-5)
Species :	Daphnia magna (Big water flea)
Effective dose :	2,6 mg/l
Exposure time :	21 D
Method :	OECD 211

Acute (short-term) toxicity to aquatic algae and cyanobacteria

Parameter :	EC50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Species :	Pseudokirchneriella subcapitata
Effective dose :	1000 mg/l
Exposure time :	7 D
Parameter :	EC50 (POLY(OXY-1,2-ETHANDIYL).ALPHA.-TRIDECYL-.OMEGA.-HDROXY-, BRANCHED ; CAS No. : 69011-36-5)
Species :	Desmodesmus subspicatus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : HP 500 Aktivreiniger (041120330000-0201)
200 L

Revision date : 16.04.2019

Version (Revision) : 21.0.0 (20.0.1)

Print date : 27.04.2020

Effective dose : > 1 mg/l
Exposure time : 72 h
Method : OECD 201

Toxicity to microorganisms

Parameter : EC50 (POLY(OXY-1,2-ETHANDIYL).ALPHA.-TRIDECYL-.OMEGA.-HDROXY-,
BRANCHED ; CAS No. : 69011-36-5)

Species : Belebtschlamm

Effective dose : 140 mg/l

Parameter : EC10 (POLY(OXY-1,2-ETHANDIYL).ALPHA.-TRIDECYL-.OMEGA.-HDROXY-,
BRANCHED ; CAS No. : 69011-36-5)

Species : Belebtschlamm

Effective dose : > 10000 mg/l

Exposure time : 17 h

Method : DIN 38412 / part 8

12.2 Persistence and degradability

Biodegradation

Parameter : Biodegradation (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)

Inoculum : Degree of elimination

Degradation rate : 96 %

Test duration : 28 D

Evaluation : Readily biodegradable (according to OECD criteria).

Parameter : Biodegradation (POLY(OXY-1,2-ETHANDIYL).ALPHA.-TRIDECYL-.OMEGA.-HDROXY-,
BRANCHED ; CAS No. : 69011-36-5)

Evaluation parameter : Aerobic

Degradation rate : > 60 %

Test duration : 28 D

Evaluation : Readily biodegradable (according to OECD criteria).

Method : OECD 301B

Parameter : Biodegradation (POLY(OXY-1,2-ETHANDIYL).ALPHA.-TRIDECYL-.OMEGA.-HDROXY-,
BRANCHED ; CAS No. : 69011-36-5)

Evaluation parameter : Anaerobic

Degradation rate : > 60 %

Test duration : 60 D

Evaluation : Biodegradable.

Method : OECD 311

Parameter : CO₂ formation (% of the theoretical value) (POLY(OXY-1,2-ETHANDIYL).ALPHA.-
TRIDECYL-.OMEGA.-HDROXY-, BRANCHED ; CAS No. : 69011-36-5)

Degradation rate : > 60 %

Test duration : 28 D

Evaluation : Readily biodegradable (according to OECD criteria).

Method : OECD 301B

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

12.3 Bioaccumulative potential

Parameter : Log KOW (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)

Value : -0,43

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : HP 500 Aktivreiniger (041120330000-0201)
200 L

Revision date : 16.04.2019

Version (Revision) : 21.0.0 (20.0.1)

Print date : 27.04.2020

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

Dispose according to legislation.

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Waste codes/waste designations according to EWC/AVV

Waste code (EWC/AVV) : 07 06 01* (aqueous washing liquids and mother liquors)

13.2 Additional information

None

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not relevant

14.8 Additional information

Land transport (ADR/RID)

No dangerous good in sense of these transport regulations.

Sea transport (IMDG)

No dangerous good in sense of these transport regulations.

Air transport (ICAO-TI / IATA-DGR)

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : HP 500 Aktivreiniger (041120330000-0201)
200 L

Revision date : 16.04.2019

Version (Revision) : 21.0.0 (20.0.1)

Print date : 27.04.2020

according to Regulation (EC) No. 1907/2006 (amended by Regulation (EU) No 830/2015)

Authorisations and/or restrictions on use

Restrictions on use

Use restriction according to REACH annex XVII, no. : 3, 40

National regulations

Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : < 5 %

Water hazard class (WGK)

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

Percentage of carcinogenic substances WGK 2 :	< 0,1 %
Percentage of carcinogenic substances WGK 3 :	< 0,1 %
Percentage of carcinogenic substances :	< 0,1 %
Percentage of substances WGK 3 :	0 %
Percentage of substances WGK 3 with M-Factor :	0 %
Percentage of substances WGK 2 :	0,22 %
Percentage of substances WGK 2 with M-Factor :	0 %
Percentage of substances WGK 1 :	21,93 %
Percentage of floating liquids :	0 %
Percentage of substances non-hazardous to water (nwg) :	77,58 %
Percentage of substances unidentified :	0 %

15.2 Chemical safety assessment

No information available.

15.3 Additional information

None

SECTION 16: Other information

16.1 Indication of changes

03. Hazardous ingredients · 07. Hints on joint storage - Storage class · 08. Occupational exposure limit values · 15. Restrictions on use · 15. Technische Anleitung Luft (TA-Luft) · 15. Water hazard class (WGK)

16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
ADR: European agreement concerning the international carriage of dangerous goods by road
(Accord européen relatif transport des marchandises dangereuses par route)
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany)
BCF: Bio-Concentration Factor
BOD(5): Biochemical oxygen demand (within 5 days)
CAS: Chemical Abstract Service
CLP: Classification, Labelling and Packaging
CMR: Carcinogenic, Mutagenic, toxic for Reproduction
DIN: German Standards Institute / German industrial norm
DNEL: Derived No Effect Level
DOC: Dissolved organic carbon
EAK/ AVV: European waste catalogue/ waste directory-regulation
EC50: Effective Concentration 50%
ECHA: European Chemical Agency
EINECS: European Inventory of Existing Commercial Chemical Substances
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : HP 500 Aktivreiniger (041120330000-0201)
200 L

Revision date : 16.04.2019

Version (Revision) : 21.0.0 (20.0.1)

Print date : 27.04.2020

IATA: International Air Transport Association
IC50: Inhibition Concentration 50%
IMDG: International Maritime Dangerous Goods Code
LC50: Lethal Concentration 50% - LD50: Lethal dose 50%
MAK: Threshold limit values Germany
NLP: No Longer Polymers
NOAEC: No Observed Adverse Effect Concentration
NOAEL: No Observed Adverse Effect Level
OECD: Organization for Economic Cooperation and Development
PBT: persistent, bioaccumulative, toxic
PC: Product category
PNEC: Predicted No Effect Concentration
REACH: Registration, Evaluation and Authorization of Chemicals
RID: Regulations concerning the international carriage of dangerous goods by rail
(Règlement International concernant le transport de marchandises dangereuses par chemin de fer)
STEL: Short-term Exposure Limit
STP: Sewage treatment plant
SVHC: Substance of Very High Concern
TLV: Threshold Limit Value
TWA: Time Weighted Average
UN: United Nations
VOC: Volatile Organic Compounds
vPvB: very persistent, very bioaccumulative

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

See SECTION 2.1 (classification).

16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.