

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Harmony in
Chemistry

Trade name : Silikonentferner (061620330000-0206)

Revision date : 08.11.2018

Print date : 24.04.2020

Version (Revision) : 16.0.0 (15.1.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Silikonentferner

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Products Category [PC]

PC 9a - Coatings and paints, thinners, paint removers

PC 0.56 - Solvent

1.3 Details of the supplier of the safety data sheet

Supplier : Chemische Werke Kluthe
Werk Oberhausen

Street : Feldstraße 55

Postal code/city : D 46149 Oberhausen

Telephone : +49208 / 9948-166

Telefax : +49208 / 9948-151

Information contact : sds.ob@kluthe.com

1.4 Emergency telephone number

+49177 / 2144737 (24 h)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

Asp. Tox. 1 ; H304 - Aspiration hazard : Category 1 ; May be fatal if swallowed and enters airways.

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Health hazard (GHS08) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

HYDROCARBONS, C9-C10, N-ALKANES, ISO-ALKANES, CYCLICS, < 2% AROMATES ; EC No. : 927-241-2

Hazard statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Harmony in
Chemistry

Trade name : Silikonentferner (061620330000-0206)

Revision date : 08.11.2018

Version (Revision) : 16.0.0 (15.1.0)

Print date : 24.04.2020

H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P101 If medical advice is needed, have product container or label at hand.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331 Do NOT induce vomiting.
P405 Store locked up.
P501 Dispose of contents/container according to local regulations

Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

Additional information

P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

ORGANIC SOLVENTS

3.2 Mixtures

Hazardous ingredients

HYDROCARBONS, C9-C10, N-ALKANES, ISO-ALKANES, CYCLICS, < 2% AROMATES ; REACH No. : 01-2119471843-32 ; EC No. : 927-241-2

Weight fraction : $\geq 75 - < 100$ %

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H336 Aquatic Chronic 3 ; H412

2-METHOXY-1-METHYLETHYL ACETATE ; REACH No. : 01-2119475791-29 ; EC No. : 203-603-9 ; CAS No. : 108-65-6

Weight fraction : $\geq 10 - < 25$ %

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336

Substance with a common (EC) occupational exposure limit value.

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH

None

This mixture contains the following substances of very high concern (SVHC) which are subject to authorisation according to Annex XIV of REACH

None

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove affected person from the danger area and lay down. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

Following inhalation

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Harmony in
Chemistry

Trade name : Silikonentferner (061620330000-0206)

Revision date : 08.11.2018

Version (Revision) : 16.0.0 (15.1.0)

Print date : 24.04.2020

Remove casualty to fresh air and keep warm and at rest. In case of respiratory tract irritation, consult a physician.

In case of skin contact

Change contaminated, saturated clothing. After contact with skin, wash immediately with plenty of water and soap. Rub greasy ointment into the skin.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Do NOT induce vomiting. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Let water be drunk in little sips (dilution effect).

4.2 Most important symptoms and effects, both acute and delayed

Dizziness Headache Impairment of vision Nausea Vomiting

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam Carbon dioxide (CO₂) Extinguishing powder Water spray jet

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Protective clothing.

5.4 Additional information

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Provide adequate ventilation. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Clear contaminated areas thoroughly.

6.4 Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13 National regulations see section 15.

SECTION 7: Handling and storage

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Harmony in
Chemistry

Trade name : Silikonentferner (061620330000-0206)

Revision date : 08.11.2018

Version (Revision) : 16.0.0 (15.1.0)

Print date : 24.04.2020



7.1 Precautions for safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Only use the material in places where open light, fire and other flammable sources can be kept away.

Protective measures

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists
Take precautionary measures against static discharges.

Measures to prevent fire

Keep away from sources of ignition - No smoking. Usual measures for fire prevention. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Provide earthing of containers, equipment, pumps and ventilation facilities. Use only antistatically equipped (spark-free) tools. Wear anti-static footwear and clothing Take precautionary measures against static discharges.

Measures to prevent aerosol and dust generation

Vapours/aerosols should be exhausted directly at the point of origin. Use only in well-ventilated areas.

Environmental precautions

Shafts and sewers must be protected from entry of the product.

7.2 Conditions for safe storage, including any incompatibilities

Hints on joint storage

Storage class (TRGS 510) : 3

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 50 ppm / 270 mg/m³

Peak limitation : 1(I)

Remark : Y

Version : 29.03.2019

Limit value type (country of origin) : STEL (EC)

Limit value : 100 ppm / 550 mg/m³

Remark : Skin

Version : 20.06.2019

Limit value type (country of origin) : TWA (EC)

Limit value : 50 ppm / 275 mg/m³

Remark : Skin

Version : 20.06.2019

DNEL-/PNEC-values

DNEL/DMEL

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Harmony in
Chemistry

Trade name : Silikonentferner (061620330000-0206)

Revision date : 08.11.2018

Version (Revision) : 16.0.0 (15.1.0)

Print date : 24.04.2020

Limit value type :	DNEL Consumer (systemic) (HYDROCARBONS, C9-C10, N-ALKANES, ISO-ALKANES, CYCLICS, < 2% AROMATES)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	300 mg/kg
Safety factor :	1 D
Limit value type :	DNEL Consumer (systemic) (HYDROCARBONS, C9-C10, N-ALKANES, ISO-ALKANES, CYCLICS, < 2% AROMATES)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	900 mg/m ³
Limit value type :	DNEL Consumer (systemic) (HYDROCARBONS, C9-C10, N-ALKANES, ISO-ALKANES, CYCLICS, < 2% AROMATES)
Exposure route :	Oral
Exposure frequency :	Long-term
Limit value :	300 mg/kg
Safety factor :	1 D
Limit value type :	DNEL worker (systemic) (HYDROCARBONS, C9-C10, N-ALKANES, ISO-ALKANES, CYCLICS, < 2% AROMATES)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	300 mg/kg
Safety factor :	1 D
Limit value type :	DNEL worker (systemic) (HYDROCARBONS, C9-C10, N-ALKANES, ISO-ALKANES, CYCLICS, < 2% AROMATES)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	1500 mg/m ³
Limit value type :	DNEL Consumer (systemic) (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Exposure route :	Oral
Exposure frequency :	Long-term
Limit value :	36 mg/kg
Limit value type :	DNEL Consumer (systemic) (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	33 mg/m ³
Limit value type :	DNEL Consumer (systemic) (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	320 mg/kg
Limit value type :	DNEL worker (local) (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Exposure route :	Inhalation
Exposure frequency :	Short-term
Limit value :	550 mg/m ³
Limit value type :	DNEL worker (systemic) (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	275 mg/m ³
Limit value type :	DNEL worker (systemic) (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Harmony in
Chemistry

Trade name : Silikonentferner (061620330000-0206)

Revision date : 08.11.2018

Version (Revision) : 16.0.0 (15.1.0)

Print date : 24.04.2020

Exposure route : 65-6)
Dermal
Exposure frequency : Long-term
Limit value : 796 mg/kg

PNEC

Limit value type : PNEC (Aquatic, freshwater) (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Limit value : 0,635 mg/l
Limit value type : PNEC (Aquatic, intermittent release) (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Limit value : 6,35 mg/l
Limit value type : PNEC (Aquatic, marine water) (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Limit value : 0,0635 mg/l
Limit value type : PNEC (Sediment, freshwater) (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Limit value : 3,29 mg/kg
Limit value type : PNEC (Sediment, marine water) (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Limit value : 0,29 mg/kg
Limit value type : PNEC (Soil) (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Limit value : 0,29 mg/kg
Limit value type : PNEC (Sewage treatment plant) (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Limit value : 100 mg/l

8.2 Exposure controls



Personal protection equipment

Eye/face protection

Eye glasses with side protection

Skin protection

Hand protection

Suitable gloves type : Gloves with long cuffs

Suitable material : Silver Shield/4H

Breakthrough time : >= 480 min

Thickness of the glove material : 0,07 mm

Recommended glove articles : EN ISO 374

Additional hand protection measures : Check leak tightness/impermeability prior to use. Do not wear gloves near rotary machines and tools. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Remark : The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Body protection

lab coat Overall

Suitable protective clothing : For the protection against direct skin contact, body protective clothing is essential

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Harmony in
Chemistry

Trade name : Silikonentferner (061620330000-0206)

Revision date : 08.11.2018

Version (Revision) : 16.0.0 (15.1.0)

Print date : 24.04.2020

(in addition to the usual working clothes). Chemical resistant safety shoes Only wear fitting, comfortable and clean protective clothing.

Required properties : antistatic. flame-resistant heat-resistant

Recommended material : Natural fibres (e.g. cotton) heat-resistant synthetic fibres

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Respiratory protection necessary at: exceeding exposure limit values / aerosol or mist formation.

Suitable respiratory protection apparatus

Filtering device (full mask or mouthpiece) with filter : A

General information

Wash hands before breaks and after work. Apply skin care products after work.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : colourless

Odour : characteristic

Safety characteristics

Melting point/freezing point :			not determined	
Initial boiling point and boiling range :	(1013 hPa)		137,0 - 165,0	°C
Decomposition temperature :			No data available	
Flash point :		approx.	29,0	°C DIN 51755 part 1
Auto-ignition temperature :			240,0	°C
Oxidising liquids :			No data available.	
Lower explosion limit :			0,6	Vol-%
Upper explosion limit :			7,0	Vol-%
Explosive properties :			No data available.	
Vapour pressure 20°C):	(20 °C)		No data available	
Density :	(20 °C)	approx.	0,767	g/cm ³
Water solubility :	(20 °C)		partially miscible	
pH-value:	(20 °C / conc.)		not applicable	
log P O/W :			No data available	
Cinematic viscosity :	(40 °C)	<	20,5	mm ² /s
Odour threshold :			No data available	
Relative vapour density :	(20 °C)		No data available	(air = 1)
Vapourisation rate :			No data available	(Ether = 1)
Maximum VOC content (EC) :	(20 °C)		100,0	Wt % gem. RL 2010/75/EG
Max. VOC content (Decopaint):	(20 °C)		100,0	Wt % gem. RL 2004/42/EG

9.2 Other information

no more data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Harmony in
Chemistry

Trade name : Silikonentferner (061620330000-0206)

Revision date : 08.11.2018

Print date : 24.04.2020

Version (Revision) : 16.0.0 (15.1.0)

10.2 Chemical stability

Stable under recommended storage and handling conditions(See section 7).

10.3 Possibility of hazardous reactions

Formation of explosive mixtures with: Air. possible

10.4 Conditions to avoid

Heat, sparks, flames and other ignition sources.

10.5 Incompatible materials

Alkali (lye), concentrated. Acid, concentrated. Oxidising agent, strong.

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Acute oral toxicity

Parameter : LD50 (HYDROCARBONS, C9-C10, N-ALKANES, ISO-ALKANES, CYCLICS, < 2% AROMATES)

Exposure route : Oral

Species : Rat

Effective dose : > 5000 mg/kg

Method : OECD 401

Parameter : LD50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)

Exposure route : Oral

Species : Rat

Effective dose : > 5000 mg/kg

Acute dermal toxicity

Parameter : LD50 (HYDROCARBONS, C9-C10, N-ALKANES, ISO-ALKANES, CYCLICS, < 2% AROMATES)

Exposure route : Dermal

Species : Rabbit

Effective dose : > 5000 mg/kg

Method : OECD 402

Parameter : LD50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)

Exposure route : Dermal

Effective dose : > 2000 mg/kg

Acute inhalation toxicity

Parameter : LC50 (HYDROCARBONS, C9-C10, N-ALKANES, ISO-ALKANES, CYCLICS, < 2% AROMATES)

Exposure route : Inhalation

Species : Rat

Effective dose : > 4951 mg/m³

Exposure time : 4 h

Method : OECD 403

Parameter : LC0 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)

Exposure route : Inhalation (vapour)

Species : Rat

Effective dose : > 20 mg/l

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Harmony in
Chemistry

Trade name : Silikonentferner (061620330000-0206)

Revision date : 08.11.2018

Print date : 24.04.2020

Version (Revision) : 16.0.0 (15.1.0)

Exposure time : 6 h

Corrosion

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2 Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

11.3 Symptoms related to the physical, chemical and toxicological characteristics

There are no data available on the preparation/mixture itself.

11.4 Other adverse effects

Prolonged or repeated contact with skin or mucous membrane result in irritation symptoms such as redness, blistering, dermatitis, etc. Has degreasing effect on the skin.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Harmful to aquatic life with long lasting effects.

Acute (short-term) fish toxicity

Parameter : NOELR (HYDROCARBONS, C9-C10, N-ALKANES, ISO-ALKANES, CYCLICS, < 2% AROMATES)

Species : Oncorhynchus mykiss (Rainbow trout)

Effective dose : 10 - 30 mg/l

Exposure time : 96 h

Parameter : LC50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)

Species : Oncorhynchus mykiss (Rainbow trout)

Effective dose : 134 mg/l

Exposure time : 96 h

Method : OECD 203

Chronic (long-term) fish toxicity

Parameter : NOEC (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)

Species : Ictalurus punctatus (Channel Catfish)

Effective dose : 47,5 mg/l

Exposure time : 14 D

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Harmony in
Chemistry

Trade name : Silikonentferner (061620330000-0206)

Revision date : 08.11.2018

Version (Revision) : 16.0.0 (15.1.0)

Print date : 24.04.2020

Method : OECD 204

Acute (short-term) toxicity to crustacea

Parameter : NOELR (HYDROCARBONS, C9-C10, N-ALKANES, ISO-ALKANES, CYCLICS, < 2% AROMATES)

Species : Daphnia magna (Big water flea)

Effective dose : 22 - 46 mg/l

Exposure time : 48 h

Parameter : EC50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)

Species : Daphnia magna (Big water flea)

Effective dose : > 500 mg/l

Exposure time : 48 h

Method : Richtlinie 67/548/EWG, Anhang V, C.2.

Chronic (long-term) toxicity to crustacea

Parameter : NOEC (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)

Species : Daphnia magna (Big water flea)

Effective dose : => 100 mg/l

Exposure time : 21 D

Method : OECD 202, Teil 2

Acute (short-term) toxicity to aquatic algae and cyanobacteria

Parameter : NOELR (HYDROCARBONS, C9-C10, N-ALKANES, ISO-ALKANES, CYCLICS, < 2% AROMATES)

Species : Pseudokirchneriella subcapitata

Effective dose : > 1000 mg/l

Exposure time : 72 h

Parameter : EC50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)

Species : Selenastrum capricornutum

Effective dose : > 1000 mg/l

Exposure time : 72 h

Method : OECD 201

Toxicity to microorganisms

Parameter : EC10 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)

Species : Belebtschlamm

Effective dose : > 1000 mg/l

Exposure time : 0,5 h

Method : OECD 209

12.2 Persistence and degradability

Biodegradation

Parameter : Biodegradation (HYDROCARBONS, C9-C10, N-ALKANES, ISO-ALKANES, CYCLICS, < 2% AROMATES)

Inoculum : Degree of elimination

Degradation rate : 89 %

Test duration : 28 D

Evaluation : Readily biodegradable (according to OECD criteria).

Parameter : Biodegradation (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)

Degradation rate : 83 %

Test duration : 28 D

Evaluation : Readily biodegradable (according to OECD criteria).

Method : OECD 301F

12.3 Bioaccumulative potential

Parameter : Log KOW (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)

Value : 0,36

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Harmony in
Chemistry

Trade name : Silikonentferner (061620330000-0206)

Revision date : 08.11.2018

Print date : 24.04.2020

Version (Revision) : 16.0.0 (15.1.0)

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

Dispose according to legislation.

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Waste codes/waste designations according to EWC/AVV

Waste code (EWC/AVV) : 07 01 04* (other organic solvents, washing liquids and mother liquors)

13.2 Additional information

None

SECTION 14: Transport information

14.1 UN number

UN 1993

14.2 UN proper shipping name

Land transport (ADR/RID)

FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C9-C10, N-ALKANES, ISO-ALKANES, CYCLICS, < 2% AROMATES · 2-METHOXY-1-METHYLETHYL ACETATE)

Sea transport (IMDG)

FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C9-C10, N-ALKANES, ISO-ALKANES, CYCLICS, < 2% AROMATES · 2-METHOXY-1-METHYLETHYL ACETATE)

Air transport (ICAO-TI / IATA-DGR)

FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C9-C10, N-ALKANES, ISO-ALKANES, CYCLICS, < 2% AROMATES · 2-METHOXY-1-METHYLETHYL ACETATE)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3
Classification code : F1
Hazard identification number (Kemler No.) : 30
Tunnel restriction code : D/E
Special provisions : LQ 5 | · E 1
Hazard label(s) : 3

Sea transport (IMDG)

Class(es) : 3
EmS-No. : F-E / S-E
Special provisions : LQ 5 | · E 1
Hazard label(s) : 3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Harmony in
Chemistry

Trade name : Silikonentferner (061620330000-0206)

Revision date : 08.11.2018

Print date : 24.04.2020

Version (Revision) : 16.0.0 (15.1.0)

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3
Special provisions : E 1
Hazard label(s) : 3

14.4 Packing group

III

14.5 Environmental hazards

Land transport (ADR/RID) : No
Sea transport (IMDG) : No
Air transport (ICAO-TI / IATA-DGR) : No

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

according to Regulation (EC) No. 1907/2006 (amended by Regulation (EU) No 830/2015)

Authorisations and/or restrictions on use

Restrictions on use

Use restriction according to REACH annex XVII, no. : 3, 40

National regulations

Water hazard class (WGK)

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

Percentage of carcinogenic substances WGK 2 :	< 0,1 %
Percentage of carcinogenic substances WGK 3 :	< 0,1 %
Percentage of carcinogenic substances :	< 0,1 %
Percentage of substances WGK 3 :	0 %
Percentage of substances WGK 3 with M-Factor :	0 %
Percentage of substances WGK 2 :	0 %
Percentage of substances WGK 2 with M-Factor :	0 %
Percentage of substances WGK 1 :	100 %
Percentage of floating liquids :	0 %
Percentage of substances non-hazardous to water (nwg) :	0 %
Percentage of substances unidentified :	0 %

15.2 Chemical safety assessment

No information available.

15.3 Additional information

None

SECTION 16: Other information

16.1 Indication of changes

02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 08. Occupational exposure limit values · 15. Restrictions on use · 15. Water hazard class (WGK)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Harmony in
Chemistry

Trade name : Silikonentferner (061620330000-0206)

Revision date : 08.11.2018

Version (Revision) : 16.0.0 (15.1.0)

Print date : 24.04.2020

16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
ADR: European agreement concerning the international carriage of dangerous goods by road
(Accord européen relatif transport des marchandises dangereuses par route)
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany)
BCF: Bio-Concentration Factor
BOD(5): Biochemical oxygen demand (within 5 days)
CAS: Chemical Abstract Service
CLP: Classification, Labelling and Packaging
CMR: Carcinogenic, Mutagenic, toxic for Reproduction
DIN: German Standards Institute / German industrial norm
DNEL: Derived No Effect Level
DOC: Dissolved organic carbon
EAK/ AVV: European waste catalogue/ waste directory-regulation
EC50: Effective Concentration 50%
ECHA: European Chemical Agency
EINECS: European Inventory of Existing Commercial Chemical Substances
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
IATA: International Air Transport Association
IC50: Inhibition Concentration 50%
IMDG: International Maritime Dangerous Goods Code
LC50: Lethal Concentration 50% - LD50: Lethal dose 50%
MAK: Treshold limit values Germany
NLP: No Longer Polymers
NOAEC: No Observed Adverse Effect Concentration
NOAEL: No Observed Adverse Effect Level
OECD: Organization for Economic Cooperation and Development
PBT: persistent, bioaccumulative, toxic
PC: Product category
PNEC: Predicted No Effect Concentration
REACH: Registration, Evaluation and Authorization of Chemicals
RID: Regulations concerning the international carriage of dangerous goods by rail
(Règlement International concernant le transport de marchandises dangereuses par chemin de fer)
STEL: Short-term Exposure Limit
STP: Sewage treatment plant
SVHC: Substance of Very High Concern
TLV: Threshold Limit Value
TWA: Time Weighted Average
UN: United Nations
VOC: Volatile Organic Compounds
vPvB: very persistent, very bioaccumulative

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

See SECTION 2.1 (classification).

16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

16.6 Training advice

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Harmony in
Chemistry

Trade name : Silikonentferner (061620330000-0206)

Revision date : 08.11.2018

Version (Revision) : 16.0.0 (15.1.0)

Print date : 24.04.2020

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
